



AD-A274 351



USAARL Report No. 93-34

(1)




Whole-body Vibration Assessment of the M9161A1 Truck Trailer

By

Al W. Moran

and

Barclay P. Butler



17508 94-00125



Impact, Tolerance, and Protection Division

August 1993

Approved for public release; distribution unlimited.

94 1 3 1 2 0

United States Army Aeromedical Research Laboratory
Fort Rucker, Alabama 36362-5292

**Best
Available
Copy**

Notice

Qualified requesters

Qualified requesters may obtain copies from the Defense Technical Information Center (DTIC), Cameron Station, Alexandria, Virginia 22314. Orders will be expedited if placed through the librarian or other person designated to request documents from DTIC.

Change of address

Organizations receiving reports from the U.S. Army Aeromedical Research Laboratory on automatic mailing lists should confirm correct address when corresponding about laboratory reports.


Disposition

Destroy this document when it is no longer needed. Do not return it to the originator.


Disclaimer


The views, opinions, and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other official documentation. Citation of trade names in this report does not constitute an official Department of the Army endorsement or approval of the use of such commercial items.

Reviewed:


JOHN V. BARSON
LTC, MC, SFS
Director, Impact, Tolerance,
and Protection Division

Released for publication:


ROGER W. WILEY, O.D., Ph.D.
Chairman, Scientific
Review Committee


DAVID H. KARNEY
Colonel, MC, SFS
Commanding

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
1a. REPORT SECURITY CLASSIFICATION Unclassified			1b. RESTRICTIVE MARKINGS		
2a. SECURITY CLASSIFICATION AUTHORITY			3. DISTRIBUTION / AVAILABILITY OF REPORT Approved for public release, distribution unlimited		
2b. DECLASSIFICATION / DOWNGRADING SCHEDULE					
4. PERFORMING ORGANIZATION REPORT NUMBER(S) USAARL Report No. 93-34			5. MONITORING ORGANIZATION REPORT NUMBER(S)		
6a. NAME OF PERFORMING ORGANIZATION U.S. Army Aeromedical Research Laboratory		6b. OFFICE SYMBOL (If applicable) SGRD-UAD-IV	7a. NAME OF MONITORING ORGANIZATION U.S. Army Medical Research and Development Command		
6c. ADDRESS (City, State, and ZIP Code) P.O. Box 620577 Fort Rucker, AL 36362-0577			7b. ADDRESS (City, State, and ZIP Code) Fort Detrick Frederick, MD 21702-5012		
8a. NAME OF FUNDING / SPONSORING ORGANIZATION		8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER		
8c. ADDRESS (City, State, and ZIP Code)			10. SOURCE OF FUNDING NUMBERS		
PROGRAM ELEMENT NO. 62787A		PROJECT NO. 30162787A878	TASK NO. GA	WORK UNIT ACCESSION NO. 132	
11. TITLE (Include Security Classification) Whole-Body Vibration Assessment of the M916A1 Truck Tractor					
12. PERSONAL AUTHOR(S) Al W. Moran, and Barclay P. Butler					
13a. TYPE OF REPORT Final		13b. TIME COVERED FROM _____ TO _____	14. DATE OF REPORT (Year, Month, Day) 1993 August		15. PAGE COUNT 164
16. SUPPLEMENTARY NOTATION					
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB-GROUP	Whole-body vibration, health hazard assessment, exposure limits, tactical vehicles, terrain, crewmembers		
23	02				
21	07				
19. ABSTRACT (Continue on reverse if necessary and identify by block number) All new tactical vehicles and aircraft are required to be evaluated for potential whole-body vibration (WBV) health hazards to their crewmembers. A health hazard assessment (HHA) was performed on the M916A1 truck tractor by the U.S. Army Aeromedical Research Laboratory, as requested by the U.S. Army Environmental Hygiene Agency. Tests were conducted at Aberdeen Proving Ground, Maryland, over paved surface, cross-country, and Belgian block terrain types. The M916A1 was tested in bobtail (no trailer), unloaded, and loaded configurations for each of the test terrains. The results of these tests show the lowest tolerance levels were experienced on the Belgian block course, with less severe WBV occurring on the cross-country course, followed by the primary terrain course. The results also show the passenger exposure limits were consistently lower than the driver's. Therefore, the HHA recommendation for the M916A1, operating in its intended environment, is that WBV be limited to the following passenger exposure limits for each test condition: WBV is not to exceed 17.1 hours in any (continued on separate sheet)					
20. DISTRIBUTION / AVAILABILITY OF ABSTRACT <input checked="" type="checkbox"/> UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT. <input type="checkbox"/> DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION Unclassified		
22a. NAME OF RESPONSIBLE INDIVIDUAL Chief, Scientific Information Center			22b. TELEPHONE (Include Area Code) 205-255-6907		22c. OFFICE SYMBOL SGRD-IJAX-ST

19. Abstract (Continued):

24-hour period on paved surfaces for all configurations. Exposure limits for the cross-country terrain are 5.5, 5.2, and 6.1 hours in any 24-hour period for the bobtail, unloaded, and loaded configurations, respectively. For the Belgian block terrain, WBV in any 24-hour period should not exceed 1 hour for both bobtail and unloaded conditions and 2 hours for the loaded configuration.

Acknowledgments

The authors would like to express their gratitude to Dr. Nabih Alem and SGT Bradley Erickson for their efforts in developing software for the data analysis. Michael Deavers and Tammy Simmons are acknowledged for their assistance with data analysis and editing. Mrs. Mary Gramling and Mr. Udo Volker Nowak also are commended for their efforts in editing this report.

DTIC QUALITY INSPECTED 6

Accession For	
NTIS GRA&I	<input checked="checked" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Avail and/or	
Dist	Special
A-1	

=====

This page intentionally left blank.

=====

Table of contents

	Page
List of figures	2
List of tables	2
Introduction	3
Methods	5
Experimental conditions	6
Instrumentation	6
Analysis	8
Results	11
Discussion	12
Conclusions	17
References	18
Appendix A: Equipment manufacturers	19
Appendix B: ISO 2631 data graphs and tables	20

List of figures

Figure	Page
1. M916A1 truck tractor configurations: (a) Bobtail, (b) unloaded trailer, (c) loaded trailer	4
2. Data acquisition system	7

List of tables

Table	Page
1. Test matrix for WBV testing of the M916A1	5
2. Hazard severity classification	9
3. Hazard probability classification	10
4. RAC determination	10
5. Driver seat HSEL for times of less than 10 hours with respect to vibration axis, vibration frequency, vehicle speed, terrain surface, and vehicle load	13
6. Passenger seat HSEL for times of less than 10 hours with respect to vibration axis, vibration frequency, vehicle speed, terrain surface, and vehicle load	15

Introduction

All new tactical vehicles and aircraft are required to be evaluated for potential whole-body vibration (WBV) health hazards to their crew members. This requirement is contained in AR 40-10, "Health Hazard Assessment Program in Support of the Army Material Acquisition Decision Process." In support of this program, the U.S. Army Aeromedical Research Laboratory (USAARL) was requested by the U.S. Army Environmental Hygiene Agency (USAEHA), Aberdeen, Maryland, to perform a health hazard assessment (HHA) on the M916A1 Truck Tractor.

The M916A1 Truck Tractor* (hereafter referred to as "M916A1") is a commercially designed, conventional cab, 6 x 6 truck tractor (Figure 1). The M916A1 is built by Freightliner Corporation, and is designed to replace the M123 Truck Tractor. It is powered by a Cummins* model NTC 400 6-cylinder diesel engine which develops 400 hp at 2100 rpm. The transmission is a Caterpillar semiautomatic gearbox with 16 forward and 2 reverse gears. The M916-series differs from the similar M915-series rear-wheel drive truck tractors by using all-wheel drive with a Oshkosh* F-U29 transfer case. The driver and passenger seats in the M916A1 are gas cylinder, air adjustable suspension buckets. The M916A1 primarily will be used with the M870 40-ton low-bed semitrailer to transport engineer construction equipment on primary, secondary, and off-road conditions.


The methods for measuring and analyzing WBV are found in the International Organization for Standardization's (ISO) guideline entitled "Guide for the Evaluation of Human Exposure to Whole-Body Vibration (ISO 2631)." ISO 2631 is reflected in MIL-STD-1472D, "Human Engineering Design Criteria for Military Systems, Equipment and Facilities." The relative severity of the processed WBV signatures are interpreted using the risk assessment codes (RAC) found in AR 40-10. These publications, as a set, define the criteria used in evaluating the WBV signatures of the M916A1.

ISO 2631 identifies three criteria for the evaluation of human exposure to WBV which can be described in terms of intensity, frequency, direction, and duration. These criteria are the preservation of comfort, the preservation of working efficiency, and the preservation of health or safety. They are known formally as the reduced comfort boundary (RCB), fatigue-decreased proficiency boundary (FDPB), and the exposure limit (EL), respectively.

* See list of manufacturers



(a)



(b)



(c)

Figure 1. M916A1 truck tractor configurations: (a) Bobtail, (b) unloaded trailer, (c) loaded trailer.

The RACs, as described in Appendix B of AR 40-10, require the classification of a health hazard according to its severity and probability. Processing vibration signatures using ISO-2631 results in measurements of vibration severity, but does not yield a measure of the probability of occurrence. RACs are obtained by combining vibration severity with the probability that the test condition will occur in a real life scenario. For vibration, RACs would be determined for each vibration amplitude at each direction and frequency.

Methods

Whole-body vibration data for the M916A1 was collected at Aberdeen Proving Ground (APG), Maryland, by the U.S. Army Combat Systems Test Activity (USACSTA) in coordination with the Response and Tolerance Branch, USAARL. A test matrix was developed that represented the planned operating environment of the M916A1 with respect to terrain type, load configuration, and vehicle speed (Table 1).

Table 1.

Test matrix for WBV testing of the M916A1.

Vehicle speed (m.p.h.)	Terrain		
	Paved surface	Cross- country	Belgian block
5			X
6		X	
8		X	
10		X	X
12		X	
15			X
20			X
25	X		
35	X		
45	X		
55	X		

Note: Each configuration shown was tested for the loaded, unloaded, and bobtail load cases.

Experimental conditions

The M916A1 was tested under three terrain conditions: primary, cross-country, and Belgian block. The primary surface was a 3-mile, smooth, level, straight, asphalt test track. The cross-country surface was a rough dirt road with numerous potholes and uneven ruts. It had been use recently for the testing of tracked vehicles. The Belgian block was an oval cobblestone road approximately 1/2-mile long with an irregular pattern of 3-inch crests. These crests were spaced such that there was no correlation between the locations of the crests for the right and left wheel track. All three courses are part of the APG test track facilities. Characterizations of these surfaces are available from APG.

The M916A1 was tested under three load conditions: bobtail, unloaded, and loaded configuration. The bobtail configuration consisted of the tractor without the trailer attached. The unloaded configuration consisted of the tractor with an empty 40-ton M870 low bed semitrailer attached. The loaded configuration consisted of the tractor with the M870 trailer attached and loaded with 80,000 lbs.

Vehicle speeds ranged from 5 to 55 m.p.h. with specific vehicle speed depending on the test terrain, and mirroring likely employment scenarios. On the paved course, the M916A1 was tested at four speeds: 25, 35, 40, and 50 m.p.h. On the cross-country course, it was tested at 6, 8, 10, and 12 m.p.h. And on the Belgian block course it was tested at four speeds: 5, 10, 15, and 20 m.p.h.

The test matrix consisted of combinations of terrain surface, load configuration, and vehicle speed, which resulted in a total of 36 vehicle runs. Seat pad accelerations were collected from the instrumented driver and passenger seat for each of the X- (fore/aft), Y- (left/right), and Z- (up/down) axes. Combinations of vehicle test runs with vibration axes yielded 216 distinct data trials.

The seats in the M916A1 were adjusted so the distance from the floor to the underside of the seat frame was 11 inches. This corresponds to a seat height at approximately one-half the possible seat stroke. The driver was 5'10" tall and weighed 156 lbs. The passenger was 6'3" tall and weighed 192 lbs.

Instrumentation

Seat pad accelerations were obtained in the X-, Y-, and Z- axes for both the driver and passenger seats. Three Endevco* model 2265C-25 accelerometers, in a triaxial arrangement, were

attached to a disk placed between the seat pad and the subject's buttocks. Each of the accelerometers were connected to a signal conditioner which provided excitation, amplification, calibration, and low pass filtering. The accelerometers were low pass filtered at 100 Hz using a six-pole Butterworth* filter. A diagram of the data acquisition system is included as Figure 2.

Filtered acceleration signals from the signal conditioner were connected to an EMR* Model 372-03 pulse code modulation (PCM) encoder. The encoder multiplexed the incoming analog signals which were then sampled at 416.67 Hz per channel. The incoming analog signal was sampled using a sample-and-hold amplifier, digitized using a 10-bit successive approximation analog-to-digital converter, and then converted to a nonreturn-to-zero level (NRZ-L) code for transmission. The encoded PCM data was then input to a Conic* Model CTL 510 transmitter for transmission at 237 MHz to the remote data handling facility. The signal conditioner, encoder, and transmitter were mounted on the back of the M916A1 cab during the entire test.

The transmitted NRZ-L code was received by a Scientific Atlanta* Series 420S receiver and passed into a Loral* Instrumentation ADS-100 system. The input buffer and PCM bit synchronizer modules recovered the serial pulse train from the data link noise and disturbances. The pulse train was recorded on a Honeywell* Model 101 PCM tape recorder along with voice annotation of the

M916A1 truck tractor data acquisition system




Figure 2. Data acquisition system.

individual test runs and an IRIG-B time code. Simultaneously, the PCM pulse train was passed to a PCM decommutator and demultiplexed into 16-bit words.

From this point, the pulse train was sent to both a digital-to-analog (D/A) converter and a parallel input module. The D/A converter passed the pulse train through a filter, external to the ADS-100 system, for real time display and fourier analysis. The parallel input module was used to input digital IRIG-B time code into the ADS-100. The pulse train passed out of the ADS-100 system from the input module to the host computer, a Hewlett-Packard* model 21MX-E series minicomputer. The data was stored temporarily on the HP system disk and later transferred to digital tape to provide a permanent storage medium. The ADS-100 system was independent of the host control; however, software residing on the minicomputer controlled the hand shaking between the ADS-100 and the HP21MX-E during data acquisition.

Analysis

Triaxial seat pad vibration data were processed using the methods prescribed in ISO 2631 for broadband signals using third-octave analysis with weighting. Digitized acceleration signals from the X-, Y-, and Z-axes, from both the driver and passenger seat pad accelerometers, were read into a Dolche* model 486 portable computer. A USAARL-developed automated analysis program was used to produce tabular and graphic plots of the acceleration data. These plots (Appendix B) were used to identify vibration exposure limits which occurred under projected normal daily operating conditions.

The RACs require classification of the health hazard according to the hazard severity and probability. Since the ISO 2631 standard does not use RACs, the severity of the hazard may be reasonably estimated from the worst-case exposure before the onset of ELs (i.e., for any vibration frequency and direction). An indicator which may be used for the assessment of hazard severity is the duration of safe exposure (DSE). The DSE is defined as the length of time a person can be exposed to WBV before reaching the health and safety exposure limit (HSEL). Thus, a long DSE indicates tolerable WBV, whereas a short DSE indicates severe WBV. In order to translate the DSEs to RACs, Table 2 was used to define the category (I-IV) of exposure.

Table 2.

Hazard severity classification.

Attribute	Category	Duration of safe exposure (DSE) to WBV
Catastrophic	I	Less than 5 minutes
Critical	II	Between 5 and 30 minutes
Marginal	III	Between 30 minutes and 4 hours
Negligible	IV	More than 4 hours

Hazard severity categories of Table 2 are defined as:

- Category I - Catastrophic: Hazard may cause death or total loss of a bodily system.**
- Category II - Critical: Hazard may cause severe bodily injury, severe occupational illness, or major damage to a bodily system.**
- Category III - Marginal: Hazard may cause minor bodily injury, minor occupational illness, or minor damage to a bodily system.**
- Category IV - Negligible: Hazard would cause less than minor bodily injury, minor occupational illness, or minor bodily system damage.**

The operational environments of the M916A1 determine the likelihood of occurrence, or probability level, of exposure to WBV. These levels, identified as levels A through E in AR 40-10, with their corresponding operating conditions relevant to the WBV signatures in the M916A1, are listed in Table 3.

Table 3.

Hazard probability classification.

Attribute	Level	Road/terrain type, operating speed
Frequent	A	Paved road, 30-50 mph cross-country, 8 mph and under
Probable	B	Cross-country, 9-16 mph paved road, under 30 mph
Occasional	C	Belgian block, under 15 mph Cross-country, above 16 mph
Remote	D	Other conditions not listed above
Improbable	E	Conditions unlikely to occur

Operating the M916A1 over paved surfaces represents approximately 75 percent of the total mission, therefore, the probability of WBV exposure over similar courses is frequent and may be assigned Level A. The operation over cross-country roads is assigned a probability Level B, which represents approximately 20 percent of its mission time. Operating over unimproved secondary roads, represented by the Belgian block, is within the M916A1 mission, but its occurrence should be only occasional, prompting the assignment of Level C to this course.

Risk assessment categories and levels are used to find the RACs for each test condition. Using Table 4, RACs are found at the intersection of a test condition category and level. The overall RAC then is found by averaging the individual RACs and rounding.

Table 4.

RAC determination.

Hazard category	Hazard probability levels				
	A	B	C	D	E
I	1	1	1	2	3
II	1	1	2	3	4
III	2	3	3	4	5
IV	3	5	5	5	5

Results

The duration of exposure necessary to reach the HSEL was calculated for all 72 data sets, each consisting of X-, Y-, and Z-axis signatures. Since the M916A1 mission requires 10 hours of operation over primary, secondary, and cross-country terrain, the exposure times of less than 10 hours were identified for assessment.

The RAC level, RAC category, and overall RAC were developed for the driver and passenger as shown in Tables 5 and 6, respectively. These tables are arranged in order of increasing values of DSE. RAC levels are a measure of the probability of occurrence of a particular test condition, and are a function of the test course, vehicle configuration, and vehicle speed as they relate to the normal mission employment of the M916A1. RAC category is a measure of the severity of the vibration exposure, and is based on the DSE. DSEs were found using the time required to reach the HSEL boundary of ISO 2631 for each exposure condition and each vibration axis (Appendix B). RAC levels and RAC categories then were combined using Table 4 to yield the overall RAC for each test condition where the DSE was less than 10 hours as shown in the last column of Tables 5 and 6.

Exposure limits for the primary, or paved, surface indicate that WBV exposures for any configuration should be limited to 17.1 hours in any 24-hour period (Appendix B, run 028). Exposure times for the cross-country surface indicate that WBV exposures should be limited to no more than 5.5 hours in a bobtail configuration (Appendix B, run 021), 5.2 hours in a no-load configuration (Appendix B, run 017), and 6.1 hours in loaded configuration (Appendix B, run 013). Exposure times for the Belgian block surface indicate WBV exposures should be limited to no more than 0.9 hours in the bobtail configuration (Appendix B, run 004), and no more than 1.4 hours in the unloaded and loaded configurations (Appendix B, runs 008 and 012).

The frequencies at which HSEL was reached consistently was in the range of 1.2 to 2.0 Hz for the driver position, which is below the whole-body resonance ranging from 4 to 8 Hz (Table 3). The passenger position showed similar results with the exception of the three high-speed runs on the Belgian block terrain (Table 4). These three test runs had frequencies of 6.4 and 8.0 Hz, within the range of WBV resonance frequency.

The vibration axes at which HSEL was reached were limited to the Y- and Z-axes. For the driver position, there were nearly equal numbers of occurrences for reaching HSEL limits for both the Y- and Z-axes. For the passenger position, HSEL limits were reached for 20 of the 23 occurrences in the Y-axis with the remainder occurring in the Z-axis.

Hazard severity was determined to be negligible for all the data trials for the driver position, and negligible or marginal for the passenger position. This resulted in a RAC category of 4 for the driver position and 3s and 4s for the passenger position. RAC exposure probability included remote, occasional, and probable for the driver position, with the passenger position results including the frequent probability. Overall RACs were 4s and 5s for the driver position, and 3s, 4s, and 5s for the passenger position. The single RAC for the M916A1 was determined by averaging the individual RACs and rounding to yield an overall RAC of 4.

Discussion

The lowest tolerance levels were experienced on the Belgian block course (0.883 and 1.833 hours for passenger and driver, respectively), with less severe WBV found under the cross-country condition (5.5 and 12.117 hours for passenger and driver, respectively), followed by the primary terrain surface (17.083 and 19.217 for passenger and driver, respectively). The Belgian block course creates repetitive axial and roll responses in the test vehicles. Vehicle roll occurred due to the out-of-phase nature of the right and left wheel track wave lengths. Typically, continuous vehicle roll is not seen in cross-country courses, and is rarely seen in primary courses. Cyclic X-axis vibration was seen in the Belgian block course and was a result of the interaction of the tractor and trailer. X-axis accelerations occurred when either the tractor or trailer was accelerated or decelerated as they rolled up or down the Belgian block wave lengths.

Vehicle configuration played a significant part in measured WBV. The M916A1 suspension system is designed to carry heavy construction equipment. When it is in a bobtail configuration, the natural frequency of the suspension system is quite high and will transmit a great deal of the WBV. A similar condition occurs when the empty trailer is attached to the tractor. Here, there is a slight lowering of the natural frequency of the suspension with most of the WBV still being transmitted into the vehicle frame. Under loaded conditions, the natural frequency of the suspension is lowered with damping seen in the lower ranges of the WBV signatures. This results in better ride quality for the vehicle crewmen. A variable suspension system that would transmit less vibration to the vehicle frame under unloaded conditions would improve vehicle ride quality.

Table 5.

Driver seat HSEL for times of less than 10 hours with respect to vibration axis, vibration frequency, vehicle speed, terrain surface, and vehicle load.

Determination of RAC category					Determination of RAC level					Overall RAC
DSE hours	Axis	Hz	Hazard severity	RAC Category	Test course	Configuration	Speed (mph)	Exposure probability	RAC level	
4.35	Z	1.2	Negligible	4	Cross-country	Bobtail	12	Probable	B	5
4.77	Z	1.6	Negligible	4	Belgian	No load	15	Remote	D	4
4.90	Z	1.6	Negligible	4	Belgian	Bobtail	15	Remote	D	5
5.22	Z	1.6	Negligible	4	Cross-country	Bobtail	12	Probable	B	5
5.35	Y	2.0	Negligible	4	Belgian	Bobtail	20	Remote	D	4
5.58	Z	1.6	Negligible	4	Cross-country	Bobtail	10	Probable	B	5
5.93	Y	1.2	Negligible	4	Belgian	Bobtail	10	Occasional	C	5
6.08	Y	1.6	Negligible	4	Belgian	Bobtail	15	Remote	D	5
6.32	Z	1.6	Negligible	4	Belgian	Loaded	20	Remote	D	5
6.35	Z	2.5	Negligible	4	Belgian	Bobtail	20	Remote	D	5
6.52	Y	2.0	Negligible	4	Belgian	No load	20	Remote	D	5
6.75	Y	1.2	Negligible	4	Belgian	No load	10	Occasional	C	5
6.95	Y	1.6	Negligible	4	Belgian	No load	15	Remote	D	5

Table 5 (Continued).

Determination of RAC category					Determination of RAC level					Overall RAC
DSE hours	Axis	Hz	Hazard severity	RAC Category	Test course	Configuration	Speed (mph)	Exposure probability	RAC level	
7.25	Z	1.6	Negligible	4	Belgian	Loaded	15	Remote	D	5
7.63	Z	1.6	Negligible	4	Belgian	No load	10	Occasional	C	5
7.81	Y	2.5	Negligible	4	Belgian	Loaded	20	Remote	D	5
8.52	Z	1.6	Negligible	4	Belgian	No load	20	Remote	D	5
8.80	Y	1.2	Negligible	4	Belgian	Loaded	10	Occasional	C	5
9.72	D	1.6	Negligible	4	Belgian	Bobtail	20	Remote	D	5

Table 6.

Passenger seat HSEL for times of less than 10 hours with respect to vibration axis, vibration frequency, vehicle speed, terrain surface, and vehicle load.

Determination of RAC category					Determination of RAC level					Overall RAC
DSE hours	Axis	Hz	Hazard severity	RAC category	Test course	Configuration	Speed (mph)	Exposure probability	RAC level	
1.25	Y	2.0	Marginal	3	Belgian	Bobtail	20	Remote	D	4
1.68	Y	1.6	Marginal	3	Belgian	Bobtail	15	Remote	D	4
1.80	Y	2.0	Marginal	3	Belgian	No load	20	Remote	D	4
1.85	Y	1.6	Marginal	3	Belgian	No load	15	Remote	D	4
2.12	Y	1.2	Marginal	3	Belgian	Bobtail	10	Occasional	C	3
2.27	Y	1.2	Marginal	3	Belgian	No load	10	Occasional	C	3
2.68	Y	2.5	Marginal	3	Belgian	Loaded	20	Remote	D	4
3.00	Y	1.6	Marginal	3	Belgian	Loaded	15	Remote	D	4
3.22	Y	1.2	Marginal	3	Belgian	Loaded	10	Occasional	C	3
4.21	Y	1.2	Negligible	4	Belgian	Bobtail	5	Occasional	C	5
4.40	Y	1.2	Negligible	4	Belgian	No load	5	Occasional	C	5
5.02	Y	1.6	Negligible	4	Belgian	Loaded	5	Occasional	C	5
6.25	Y	1.2	Negligible	4	Cross-country	Bobtail	12	Probable	B	5
6.58	Y	1.2	Negligible	4	Cross-country	Bobtail	12	Probable	B	5
7.68	Z	8.0	Negligible	4	Belgian	Bobtail	20	Remote	D	5

Table 6 (Continued).

Determination of RAC category					Determination of RAC level					Overall RAC
DSE hours	Axis	Hz	Hazard severity	RAC cate-gory	Test course	Configu-ration	Speed (mph)	Exposure probability	RAC level	
7.68	Z	6.4	Negligible	4	Belgian	Loaded	20	Remote	D	5
8.02	Y	1.6	Negligible	4	Cross-country	No load	6	Frequent	A	3
8.80	Y	1.2	Negligible	4	Cross-country	Bobtail	10	Probable	B	5
8.80	Y	1.2	Negligible	4	Cross-country	No load	10	Probable	B	5
9.10	Y	1.6	Negligible	4	Cross-country	Bobtail	6	Frequent	A	3
9.10	Y	1.6	Negligible	4	Cross-country	Bobtail	8	Frequent	A	3
9.40	Z	8.0	Negligible	4	Belgian	Bobtail	15	Remote	D	5
9.72	Y	1.6	Negligible	4	Cross-country	No load	8	Frequent	A	3

The WBV experienced by the vehicle crewmen differed for seating position. The passenger position data typically showed a lower EL as compared to the driver position for most of the data trails. This situation is most apparent under the Belgian block surface where vehicle roll occurred. A likely reason for this result is that the passenger does not have hand holds which can be used to dampen WBV. By grabbing the steering wheel, the driver can reduce the amount of upper body sway. This, in turn, lowers the amount of induced seat motion resulting in a lower apparent WBV measurement at that seating position. The addition of both right and left hand holds for the passenger would reduce the amount of vibration measured at that position and likely would improve the perceived ride quality.

Conclusions

While operating the M916A1 in its intended operational environment, both driver and passenger were exposed to an overall RAC of 4. This consisted of an overall assignment of hazard severity category III and hazard probability level C. It is recommended that exposure to WBV be restricted to:

- a. Paved surface: All vehicle configurations, not more than 17.1 continuous hours in any 24-hour period.
- b. Cross-country terrain: Bobtail configuration, not more than 5.5 continuous hours in any 24-hour period.
- c. Cross-country terrain: Unloaded trailer, not more than 5.2 continuous hours in any 24-hour period.
- d. Cross-country terrain: Loaded trailer, not more than 6.1 continuous hours in any 24-hour period.
- e. Belgian block: Bobtail and unloaded configuration, not more than 0.9 continuous hours in any 24-hour period.
- f. Belgian block: Loaded configuration, not more than 1.4 continuous hours in any 24-hour period.

References

Department of the Army. 1991. Production qualification test - Government (POT-G) of truck tractor, commercial, M915A1 and M916A1. Washington, DC: Department of the Army. USACSTA Report No. 7111. Vols. I and II.

Department of the Army. 1991. Health hazard assessment program in support of the Army material acquisition decision process. Washington, DC: Department of the Army. AR 40-10.

Department of Defense. 1989. Human engineering design criteria for Military systems, equipment and facilities. Washington, DC: Department of Defense. MIL-STS-1472D.

International Organization for Standardization. 1985. Evaluation of human exposure to whole-body vibration, Part 1: General requirements. ISO-2631. 2nd edition. 1985-05-15.

Appendix A.

Manufacturer's list.

Conic/Loral Data Systems
9020 Balboa Avenue
San Diego, CA 92123

EMR/Fairchild Weston Systems
P.O. Box 3041
Sarasota, FL 33578

Freightliner Corporation
P.O. Box 3849
Portland, OR 97208

Honeywell
Honeywell Plaza
Minneapolis, MN 55408

Hewlett-Packard Company
4700 Bayou Boulevard
Pensacola, FL 32502

Larson-Davis Laboratories
280 South Main
Pleasant Grove, UT 84062

Loral Instrumentation
8401-T Aero Dr.
San Diego, CA 92123

Scientific Atlanta
1-T Technology Parkway
P.O. Box 105600
Atlanta, GA 30348

TEAC Corporation of America
7733 Telegraph Road
Montebello, CA 90640

Appendix B.

ISO 2631 graphs

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-01 Passenger

19-AUG-93 8:21:57

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Belgian block
4: Position:..... Passenger
5: Speed:..... 5 mph
6: Note:..... Bobtail

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.5200	0.5200	0.217	2.350	6.583
4.07	1.0300	0.5059	0.233	2.450	6.833
2.56	0.5300	0.4142	0.367	3.350	8.967
1.52	0.3800	0.3800	0.517	3.817	10.067
5.12	0.8600	0.3360	0.617	4.583	11.833

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.04	0.9900	0.9900	0.017	0.717	2.533
1.24	0.8000	0.8000	0.017	1.133	3.517
1.52	0.6200	0.6200	0.183	1.767	5.133
1.98	0.5200	0.5200	0.217	2.350	6.583
7.95	1.5000	0.3772	0.517	3.867	10.150

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.4400	0.3099	1.433	8.233	20.000
4.07	0.2900	0.2900	1.617	9.000	21.683
7.95	0.2800	0.2800	1.700	9.433	22.617
2.56	0.3500	0.2800	1.700	9.433	22.617
5.12	0.2700	0.2700	1.817	9.900	23.617

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary

Fatigue ... Fatigue-decreased proficiency boundary

Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-01 Driver

19-AUG-93 8:21:57

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Belgian block
4: Position:..... Driver
5: Speed:..... 5 mph
6: Note:..... Bobtail

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
4.07	0.8000	0.3929	0.450	3.633	9.617
1.98	0.2500	0.2500	1.167	6.967	17.217
2.56	0.3100	0.2423	1.233	7.283	17.867
5.12	0.5800	0.2266	1.383	7.967	19.433
1.52	0.1700	0.1700	2.233	11.683	27.433

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.04	0.5200	0.5200	0.217	2.350	6.583
1.24	0.4300	0.4300	0.333	3.167	8.533
1.52	0.3800	0.3800	0.517	3.817	10.067
1.98	0.3500	0.3500	0.567	4.317	11.217
7.95	0.7900	0.1987	1.733	9.517	22.800

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
4.07	0.4000	0.4000	0.867	5.783	14.550
1.98	0.4700	0.3311	1.283	7.517	18.433
5.12	0.3100	0.3100	1.433	8.217	20.000
2.56	0.3700	0.2960	1.550	8.750	21.117
1.52	0.3600	0.2218	2.500	12.800	29.800

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary

Fatigue ... Fatigue-decreased proficiency boundary

Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-02 Passenger

19-AUG-93 8:21:58

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Belgian block
4: Position:..... Passenger
5: Speed:..... 10 mph
6: Note:..... Bobtail

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.5200	0.5200	0.217	2.350	6.583
1.52	0.3900	0.3900	0.467	3.667	9.717
2.56	0.4600	0.3595	0.533	4.150	10.833
4.07	0.6600	0.3242	0.667	4.833	12.383
1.24	0.3100	0.3100	0.717	5.150	13.117

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.24	1.5300	1.5300	0.017	0.250	1.217
1.04	1.5100	1.5100	0.017	0.267	1.250
1.52	1.2400	1.2400	0.017	0.467	1.750
1.98	0.5400	0.5400	0.200	2.217	6.250
7.95	2.0700	0.5205	0.217	2.350	6.567

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.4700	0.3311	1.283	7.517	18.433
7.95	0.3300	0.3300	1.283	7.550	18.500
2.56	0.3700	0.2960	1.550	8.750	21.117
1.52	0.4500	0.2772	1.733	9.550	22.867
6.35	0.2500	0.2500	2.067	10.967	25.867

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-02 Driver

19-AUG-93 8:21:58

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Belgian block
4: Position:..... Driver
5: Speed:..... 10 mph
6: Note:..... Bobtail

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.3000	0.3000	0.783	5.400	13.683
2.56	0.3200	0.2501	1.167	6.967	17.183
3.22	0.3400	0.2113	1.550	8.750	21.150
4.07	0.4300	0.2112	1.550	8.767	21.183
1.52	0.2000	0.2000	1.700	9.433	22.617

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.24	0.8300	0.8300	0.017	1.067	3.333
1.04	0.7900	0.7900	0.017	1.167	3.583
1.52	0.7400	0.7400	0.017	1.300	3.967
1.98	0.3600	0.3600	0.533	4.133	10.800
7.95	1.1700	0.2942	0.817	5.550	14.017

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.5100	0.3592	1.100	6.717	16.650
1.52	0.5100	0.3142	1.400	8.083	19.650
2.56	0.3900	0.3119	1.417	8.150	19.833
4.07	0.2700	0.2700	1.817	9.900	23.617
7.95	0.2600	0.2600	1.933	10.400	24.683

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-03 Passenger

19-AUG-93 8:21:58

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Belgian block
4: Position:..... Passenger
5: Speed:..... 15 mph
6: Note:..... Bobtail

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
4.07	1.7000	0.8350	0.017	1.050	3.300
1.98	0.8200	0.8200	0.017	1.083	3.400
1.52	0.8000	0.8000	0.017	1.133	3.517
3.22	1.0600	0.6589	0.017	1.600	4.700
7.95	2.3500	0.5909	0.183	1.917	5.500

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	1.8600	1.8600	0.017	0.183	0.800
1.98	1.3600	1.3600	0.017	0.333	1.500
1.24	1.1400	1.1400	0.017	0.533	2.017
1.04	0.7500	0.7500	0.017	1.267	3.883
7.95	2.9400	0.7393	0.017	1.300	3.967

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	1.0000	0.6654	0.267	2.717	7.450
1.98	0.9400	0.6621	0.267	2.733	7.500
4.07	0.5900	0.5900	0.350	3.267	8.767
7.95	0.5300	0.5300	0.517	3.833	10.117
3.22	0.4900	0.4395	0.700	5.050	12.900

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary

Fatigue ... Fatigue-decreased proficiency boundary

Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-03 Driver

19-AUG-93 8:21:58

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Belgian block
4: Position:..... Driver
5: Speed:..... 15 mph
6: Note:..... Bobtail

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
4.07	1.0500	0.5157	0.217	2.383	6.650
1.98	0.4700	0.4700	0.267	2.767	7.567
3.22	0.7500	0.4662	0.267	2.800	7.650
1.52	0.3800	0.3800	0.517	3.817	10.067
7.95	1.1700	0.2942	0.817	5.550	14.017

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	1.1600	1.1600	0.017	0.517	1.967
1.98	0.9400	0.9400	0.017	0.783	2.750
1.24	0.6500	0.6500	0.017	1.633	4.800
7.95	1.7600	0.4426	0.317	3.033	8.217
1.04	0.4100	0.4100	0.383	3.400	9.100

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
4.07	0.7200	0.7200	0.217	2.400	6.683
1.98	0.7900	0.5565	0.433	3.567	9.483
1.52	0.8500	0.5237	0.517	3.917	10.267
3.22	0.5600	0.5023	0.533	4.167	10.867
7.95	0.3700	0.3700	1.050	6.450	16.050

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-04 Passenger

19-AUG-93 8:21:59

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Belgian block
4: Position:..... Passenger
5: Speed:..... 20 mph
6: Note:..... Bobtail

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.8800	0.8800	0.017	0.917	3.050
4.07	1.6800	0.8252	0.017	1.067	3.367
1.52	0.7300	0.7300	0.017	1.333	4.050
3.22	1.0200	0.6340	0.017	1.700	4.967
7.95	2.0600	0.5180	0.217	2.367	6.617

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	1.7800	1.7800	0.017	0.183	0.883
1.52	1.5600	1.5600	0.017	0.250	1.183
2.56	1.4200	1.1097	0.017	0.567	2.117
1.24	0.8000	0.8000	0.017	1.133	3.517
7.95	3.0700	0.7720	0.017	1.217	3.717

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.9600	0.6762	0.250	2.650	7.283
7.95	0.5100	0.5100	0.517	4.067	10.650
4.07	0.5100	0.5100	0.517	4.067	10.650
2.56	0.6100	0.4879	0.567	4.350	11.267
1.52	0.7400	0.4559	0.650	4.800	12.300

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-04 Driver

19-AUG-93 8:21:59

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Belgian block
4: Position:..... Driver
5: Speed:..... 20 mph
6: Note:..... Bobtail

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.5000	0.5000	0.233	2.500	6.950
4.07	0.9900	0.4863	0.250	2.617	7.217
3.22	0.7200	0.4475	0.300	2.983	8.083
1.52	0.3600	0.3600	0.533	4.133	10.800
2.56	0.3200	0.2501	1.167	6.967	17.183

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	1.2100	1.2100	0.017	0.517	1.833
1.52	1.0000	1.0000	0.017	0.700	2.500
2.56	0.9000	0.7034	0.017	1.417	4.267
1.24	0.4900	0.4900	0.250	2.583	7.150
7.95	1.8600	0.4677	0.267	2.783	7.617

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	1.0300	0.7255	0.217	2.367	6.617
4.07	0.6100	0.6100	0.317	3.100	8.383
1.52	0.7900	0.4867	0.567	4.367	11.300
3.22	0.4800	0.4305	0.733	5.200	13.250
2.56	0.5200	0.4159	0.800	5.467	13.833

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-05 Passenger

19-AUG-93 8:22:00

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Belgian block
4: Position:..... Passenger
5: Speed:..... 5 mph
6: Note:..... Unloaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
4.07	0.8200	0.4028	0.417	3.500	9.317
1.98	0.3300	0.3300	0.633	4.700	12.117
3.22	0.4900	0.3046	0.750	5.283	13.400
2.56	0.3600	0.2813	0.883	5.917	14.833
5.12	0.6000	0.2345	1.300	7.617	18.617

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	0.8200	0.8200	0.017	1.083	3.400
1.04	0.7700	0.7700	0.017	1.217	3.733
1.24	0.6500	0.6500	0.017	1.633	4.800
1.98	0.5600	0.5600	0.200	2.083	5.933
4.07	0.5600	0.2751	0.933	6.100	15.250

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.4100	0.2888	1.617	9.050	21.800
7.95	0.2800	0.2800	1.700	9.433	22.617
2.56	0.3400	0.2720	1.800	9.800	23.433
4.07	0.2500	0.2500	2.067	10.967	25.867
5.12	0.1900	0.1900	3.183	15.583	35.683

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-05 Driver

19-AUG-93 8:22:00

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Belgian block
4: Position:..... Driver
5: Speed:..... 5 mph
6: Note:..... Unloaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
4.07	0.5200	0.2554	1.117	6.767	16.750
3.22	0.3400	0.2113	1.550	8.750	21.150
2.56	0.2100	0.1641	2.367	12.217	28.617
1.98	0.1600	0.1600	2.450	12.617	29.500
5.12	0.3300	0.1289	3.433	16.617	37.867

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	0.5100	0.5100	0.233	2.433	6.750
1.04	0.4600	0.4600	0.283	2.850	7.783
1.24	0.3900	0.3900	0.467	3.667	9.717
1.98	0.3500	0.3500	0.567	4.317	11.217
2.56	0.1800	0.1407	3.000	14.867	34.250

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.4000	0.2818	1.683	9.350	22.433
4.07	0.2600	0.2600	1.933	10.400	24.683
2.56	0.3100	0.2480	2.083	11.083	26.117
1.52	0.3200	0.1971	3.000	14.867	34.183
3.22	0.2100	0.1883	3.217	15.750	36.050

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary

Fatigue ... Fatigue-decreased proficiency boundary

Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-06 Passenger

19-AUG-93 8:22:00

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Belgian block
4: Position:..... Passenger
5: Speed:..... 10 mph
6: Note:..... Unloaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.7200	0.4475	0.300	2.983	8.083
1.98	0.4000	0.4000	0.417	3.533	9.400
2.56	0.4800	0.3751	0.517	3.900	10.250
4.07	0.6000	0.2947	0.800	5.533	14.000
1.52	0.2700	0.2700	0.967	6.267	15.617

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.04	1.0600	1.0600	0.017	0.617	2.267
1.24	0.9500	0.9500	0.017	0.767	2.700
1.52	0.8100	0.8100	0.017	1.117	3.450
1.98	0.6200	0.6200	0.183	1.767	5.133
3.22	0.6500	0.4040	0.417	3.483	9.267

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.5000	0.3522	1.150	6.900	17.083
2.56	0.4100	0.3279	1.300	7.617	18.650
7.95	0.3200	0.3200	1.367	7.883	19.217
3.22	0.3000	0.2691	1.817	9.933	23.717
1.52	0.4300	0.2649	1.867	10.150	24.183

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary

Fatigue ... Fatigue-decreased proficiency boundary

Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-06 Driver

19-AUG-93 8:22:00

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Belgian block
4: Position:..... Driver
5: Speed:..... 10 mph
6: Note:..... Unloaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.4800	0.2984	0.783	5.433	13.767
2.56	0.3100	0.2423	1.233	7.283	17.867
1.98	0.2300	0.2300	1.350	7.817	19.050
4.07	0.3800	0.1866	1.917	10.333	24.550
7.95	0.5300	0.1333	3.267	15.933	36.433

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.04	0.6300	0.6300	0.183	1.717	5.017
1.24	0.5700	0.5700	0.183	2.033	5.783
1.52	0.5000	0.5000	0.233	2.500	6.950
1.98	0.3800	0.3800	0.517	3.817	10.067
7.95	0.7800	0.1961	1.767	9.683	23.150

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.5400	0.3804	0.950	6.200	15.500
1.52	0.4900	0.3019	1.500	8.517	20.617
2.56	0.3600	0.2880	1.633	9.083	21.867
3.22	0.2700	0.2422	2.167	11.417	26.867
4.07	0.2100	0.2100	2.717	13.717	31.750

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary

Fatigue ... Fatigue-decreased proficiency boundary

Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-07 Passenger

19-AUG-93 8:22:01

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Belgian block
4: Position:..... Passenger
5: Speed:..... 15 mph
6: Note:..... Unloaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	1.0000	0.6216	0.183	1.750	5.117
4.07	1.1200	0.5501	0.200	2.150	6.083
1.98	0.5100	0.5100	0.233	2.433	6.750
2.56	0.5700	0.4455	0.300	3.000	8.133
1.52	0.4000	0.4000	0.417	3.533	9.400

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	1.2000	1.2000	0.017	0.517	1.850
1.98	1.1600	1.1600	0.017	0.517	1.967
1.24	0.8600	0.8600	0.017	0.950	3.150
1.04	0.6800	0.6800	0.017	1.517	4.483
7.95	2.2400	0.5633	0.183	2.067	5.883

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	0.8700	0.5360	0.517	3.783	9.967
1.98	0.7400	0.5212	0.517	3.933	10.333
7.95	0.4600	0.4600	0.633	4.733	12.183
3.22	0.4000	0.3588	1.117	6.733	16.683
4.07	0.3400	0.3400	1.217	7.250	17.833

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary

Fatigue ... Fatigue-decreased proficiency boundary

Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-07 Driver

19-AUG-93 8:22:01

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Belgian block
4: Position:..... Driver
5: Speed:..... 15 mph
6: Note:..... Unloaded trailer

Third-octave bands with greatest weighted RMS accelerations (m/s²) Durations of WBV exposure before reaching ISO limits*

X: Longitudinal

Comfort Fatigue Health

(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.5900	0.3667	0.517	4.033	10.550
1.98	0.2900	0.2900	0.833	5.667	14.267
4.07	0.5900	0.2898	0.833	5.667	14.300
2.56	0.3100	0.2423	1.233	7.283	17.867
7.95	0.8400	0.2112	1.550	8.767	21.183

Y: Transverse

Comfort Fatigue Health

(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.7200	0.7200	0.017	1.367	4.133
1.52	0.7200	0.7200	0.017	1.367	4.133
1.24	0.5200	0.5200	0.217	2.350	6.583
1.04	0.4100	0.4100	0.383	3.400	9.100
7.95	1.3500	0.3395	0.600	4.517	11.667

Z: Vertical

Comfort Fatigue Health

(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.7100	0.5001	0.533	4.183	10.917
1.52	0.7600	0.4682	0.617	4.617	11.900
4.07	0.3700	0.3700	1.050	6.450	16.050
3.22	0.4000	0.3588	1.117	6.733	16.683
7.95	0.2700	0.2700	1.817	9.900	23.617

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-08 Passenger

19-AUG-93 8:22:01

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Belgian block
4: Position:..... Passenger
5: Speed:..... 20 mph
6: Note:..... Unloaded trailer

Third-octave bands with greatest
weighted RMS accelerations (m/s²)

Durations of WBV exposure
before reaching ISO limits*

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
4.07	1.1900	0.5845	0.183	1.950	5.583
3.22	0.9200	0.5718	0.183	2.017	5.750
1.98	0.5700	0.5700	0.183	2.033	5.783
2.56	0.6000	0.4689	0.267	2.767	7.583
7.95	1.8600	0.4677	0.267	2.783	7.617

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	1.4100	1.4100	0.017	0.300	1.417
1.52	1.2700	1.2700	0.017	0.417	1.683
2.56	1.2900	1.0081	0.017	0.683	2.467
1.24	0.7200	0.7200	0.017	1.367	4.133
3.22	1.0200	0.6340	0.017	1.700	4.967

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.8400	0.5917	0.350	3.250	8.733
1.52	0.7700	0.4744	0.600	4.533	11.683
7.95	0.4400	0.4400	0.700	5.050	12.900
2.56	0.5400	0.4319	0.733	5.183	13.183
3.22	0.4300	0.3857	0.933	6.083	15.250

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-08 Driver

19-AUG-93 8:22:01

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Belgian block
4: Position:..... Driver
5: Speed:..... 20 mph
6: Note:..... Unloaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)** **Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.5500	0.3419	0.583	4.467	11.550
1.98	0.3300	0.3300	0.633	4.700	12.117
4.07	0.5900	0.2898	0.833	5.667	14.300
6.35	0.8300	0.2612	1.067	6.550	16.300
2.56	0.3300	0.2579	1.100	6.683	16.550

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.9000	0.9000	0.017	0.867	2.950
1.52	0.7900	0.7900	0.017	1.167	3.583
2.56	0.7600	0.5939	0.183	1.900	5.450
1.24	0.4400	0.4400	0.317	3.050	8.267
6.35	1.1000	0.3462	0.567	4.383	11.367

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.8000	0.5635	0.417	3.500	9.333
1.52	0.6700	0.4128	0.800	5.533	14.000
3.22	0.4400	0.3946	0.883	5.900	14.800
4.07	0.3700	0.3700	1.050	6.450	16.050
2.56	0.4600	0.3679	1.067	6.500	16.183

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-09 Passenger

19-AUG-93 8:22:02

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Belgian block
4: Position:..... Passenger
5: Speed:..... 5 mph
6: Note:..... Loaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.3600	0.3600	0.533	4.133	10.800
2.56	0.3400	0.2657	1.000	6.400	15.933
3.22	0.4100	0.2548	1.117	6.783	16.800
1.52	0.2000	0.2000	1.700	9.433	22.617
6.35	0.5100	0.1605	2.450	12.583	29.367

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	0.8100	0.8100	0.017	1.117	3.450
1.98	0.6400	0.6400	0.017	1.667	4.900
1.24	0.6100	0.6100	0.183	1.817	5.250
1.04	0.5500	0.5500	0.200	2.150	6.083
2.56	0.2500	0.1954	1.767	9.733	23.250

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.4800	0.3381	1.233	7.300	17.967
2.56	0.3300	0.2640	1.883	10.200	24.250
3.22	0.2600	0.2332	2.300	12.000	28.117
1.52	0.3400	0.2095	2.733	13.750	31.867
7.95	0.1900	0.1900	3.183	15.583	35.683

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-09 Driver

19-AUG-93 8:22:02

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Belgian block
4: Position:..... Driver
5: Speed:..... 5 mph
6: Note:..... Loaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)** **Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.2000	0.2000	1.700	9.433	22.617
2.56	0.2000	0.1563	2.550	13.000	30.300
3.22	0.2400	0.1492	2.750	13.800	32.000
1.52	0.1100	0.1100	4.350	20.183	45.250
7.95	0.3200	0.0805	6.800	29.367	64.000

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	0.4900	0.4900	0.250	2.583	7.150
1.98	0.4000	0.4000	0.417	3.533	9.400
1.24	0.3500	0.3500	0.567	4.317	11.217
1.04	0.3100	0.3100	0.717	5.150	13.117
2.56	0.1600	0.1250	3.600	17.250	39.183

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.4700	0.3311	1.283	7.517	18.433
1.52	0.3900	0.2403	2.200	11.550	27.117
2.56	0.2700	0.2160	2.600	13.250	30.750
3.22	0.2100	0.1883	3.217	15.750	36.050
6.35	0.1400	0.1400	5.000	22.683	50.367

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-10 Passenger

19-AUG-93 8:22:02

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Belgian block
4: Position:..... Passenger
5: Speed:..... 10 mph
6: Note:..... Loaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.5900	0.4611	0.283	2.850	7.767
3.22	0.6600	0.4102	0.383	3.400	9.083
1.98	0.3500	0.3500	0.567	4.317	11.217
1.52	0.2700	0.2700	0.967	6.267	15.617
6.35	0.8100	0.2549	1.117	6.783	16.800

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.24	0.7900	0.7900	0.017	1.167	3.583
1.52	0.7700	0.7700	0.017	1.217	3.733
1.04	0.7500	0.7500	0.017	1.267	3.883
1.98	0.7300	0.7300	0.017	1.333	4.050
2.56	0.3300	0.2579	1.100	6.683	16.550

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.4900	0.3451	1.183	7.100	17.500
2.56	0.4100	0.3279	1.300	7.617	18.650
5.12	0.3200	0.3200	1.367	7.883	19.217
6.35	0.3000	0.3000	1.517	8.600	20.800
3.22	0.2900	0.2601	1.933	10.400	24.683

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary

Fatigue ... Fatigue-decreased proficiency boundary

Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-10 Driver

19-AUG-93 8:22:02

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Belgian block
4: Position:..... Driver
5: Speed:..... 10 mph
6: Note:..... Loaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal

Comfort

Fatigue

Health

(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.3600	0.2813	0.883	5.917	14.833
3.22	0.4000	0.2486	1.167	7.017	17.333
1.98	0.1700	0.1700	2.233	11.683	27.433
6.35	0.4200	0.1322	3.300	16.083	36.750
7.95	0.4600	0.1157	4.050	19.000	42.800

Y: Transverse

Comfort

Fatigue

Health

(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	0.4800	0.4800	0.250	2.667	7.350
1.98	0.4700	0.4700	0.267	2.767	7.567
1.24	0.4700	0.4700	0.267	2.767	7.567
1.04	0.4500	0.4500	0.300	2.950	8.017
2.56	0.1800	0.1407	3.000	14.867	34.250

Z: Vertical

Comfort

Fatigue

Health

(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.5200	0.3663	1.067	6.550	16.250
1.52	0.4500	0.2772	1.733	9.550	22.867
2.56	0.3200	0.2560	1.983	10.617	25.183
5.12	0.2100	0.2100	2.717	13.717	31.750
3.22	0.2200	0.1973	3.000	14.833	34.183

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary

Fatigue ... Fatigue-decreased proficiency boundary

Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-11 Passenger

19-AUG-93 8:22:03

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Belgian block
4: Position:..... Passenger
5: Speed:..... 15 mph
6: Note:..... Loaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.3700	0.3700	0.517	3.967	10.433
2.56	0.4700	0.3673	0.517	4.017	10.517
7.95	1.4300	0.3596	0.533	4.150	10.833
3.22	0.5100	0.3170	0.683	4.983	12.750
6.35	0.9700	0.3053	0.750	5.267	13.367

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	1.2400	1.2400	0.017	0.467	1.750
1.98	1.0700	1.0700	0.017	0.600	2.233
1.24	0.6900	0.6900	0.017	1.467	4.400
1.04	0.5200	0.5200	0.217	2.350	6.583
3.22	0.7200	0.4475	0.300	2.983	8.083

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	0.8200	0.5052	0.533	4.133	10.767
1.98	0.6300	0.4438	0.700	4.983	12.750
7.95	0.3400	0.3400	1.217	7.250	17.833
5.12	0.3400	0.3400	1.217	7.250	17.833
4.07	0.2800	0.2800	1.700	9.433	22.617

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-11 Driver

19-AUG-93 8:22:03

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Belgian block
4: Position:..... Driver
5: Speed:..... 15 mph
6: Note:..... Loaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)** **Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.3000	0.2345	1.300	7.617	18.617
1.98	0.2000	0.2000	1.700	9.433	22.617
3.22	0.3000	0.1865	1.917	10.350	24.617
7.95	0.6200	0.1559	2.567	13.050	30.367
1.52	0.1400	0.1400	3.033	14.967	34.433

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	0.7600	0.7600	0.017	1.250	3.800
1.98	0.6800	0.6800	0.017	1.517	4.483
1.24	0.4100	0.4100	0.383	3.400	9.100
1.04	0.2900	0.2900	0.833	5.667	14.267
2.56	0.3200	0.2501	1.167	6.967	17.183

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	0.8100	0.4990	0.533	4.200	10.950
1.98	0.6600	0.4649	0.633	4.667	12.000
5.12	0.2900	0.2900	1.617	9.000	21.683
2.56	0.3300	0.2640	1.883	10.200	24.250
4.07	0.2400	0.2400	2.200	11.550	27.183

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-12 Passenger

19-AUG-93 8:22:03

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Belgian block
4: Position:..... Passenger
5: Speed:..... 20 mph
6: Note:..... Loaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
5.12	1.1600	0.4533	0.300	2.917	7.950
7.95	1.6900	0.4250	0.350	3.233	8.667
2.56	0.5100	0.3986	0.433	3.550	9.450
1.98	0.3900	0.3900	0.467	3.667	9.717
3.22	0.5800	0.3605	0.533	4.133	10.800

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	1.3800	1.3800	0.017	0.317	1.467
1.52	0.9900	0.9900	0.017	0.717	2.533
1.24	0.7400	0.7400	0.017	1.300	3.967
2.56	0.8500	0.6643	0.017	1.567	4.650
1.04	0.5600	0.5600	0.200	2.083	5.933

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.9000	0.6339	0.300	2.933	7.967
5.12	0.4600	0.4600	0.633	4.733	12.183
1.52	0.7400	0.4559	0.650	4.800	12.300
2.56	0.4800	0.3839	0.933	6.133	15.333
7.95	0.3300	0.3300	1.283	7.550	18.500

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-12 Driver

19-AUG-93 8:22:03

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Belgian block
4: Position:..... Driver
5: Speed:..... 20 mph
6: Note:..... Loaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.3600	0.2813	0.883	5.917	14.833
1.98	0.2500	0.2500	1.167	6.967	17.217
3.22	0.3500	0.2176	1.483	8.433	20.433
7.95	0.8400	0.2112	1.550	8.767	21.183
5.12	0.4900	0.1915	1.833	10.000	23.800

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.9000	0.9000	0.017	0.867	2.950
1.52	0.5800	0.5800	0.183	1.967	5.650
1.24	0.4300	0.4300	0.333	3.167	8.533
2.56	0.5400	0.4220	0.350	3.267	8.750
1.04	0.3300	0.3300	0.633	4.700	12.117

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.8300	0.5846	0.367	3.317	8.867
1.52	0.7400	0.4559	0.650	4.800	12.300
5.12	0.4500	0.4500	0.667	4.883	12.517
6.35	0.3000	0.3000	1.517	8.600	20.800
7.95	0.2600	0.2600	1.933	10.400	24.683

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-13 Passenger

19-AUG-93 8:22:04

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Cross country #2
4: Position:..... Passenger
5: Speed:..... 12 mph
6: Note:..... Loaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)** **Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.6100	0.3792	0.517	3.833	10.083
2.56	0.3800	0.2970	0.800	5.467	13.867
1.98	0.2500	0.2500	1.167	6.967	17.217
6.35	0.6100	0.1920	1.833	9.967	23.750
7.95	0.7200	0.1811	2.017	10.750	25.500

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	0.5500	0.5500	0.200	2.150	6.083
1.98	0.5400	0.5400	0.200	2.217	6.250
1.24	0.4900	0.4900	0.250	2.583	7.150
1.04	0.4500	0.4500	0.300	2.950	8.017
2.56	0.3700	0.2892	0.833	5.683	14.333

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.4300	0.3029	1.500	8.500	20.550
1.52	0.4300	0.2649	1.867	10.150	24.183
2.56	0.3100	0.2480	2.083	11.083	26.117
6.35	0.2300	0.2300	2.350	12.217	28.550
3.22	0.2500	0.2242	2.450	12.617	29.433

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-13 Driver

19-AUG-93 8:22:04

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Cross country #2
4: Position:..... Driver
5: Speed:..... 12 mph
6: Note:..... Loaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal

Comfort Fatigue Health

(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.3900	0.2424	1.233	7.267	17.867
2.56	0.2500	0.1954	1.767	9.733	23.250
1.98	0.1300	0.1300	3.400	16.433	37.500
1.52	0.1000	0.1000	5.000	22.683	50.367
7.95	0.3700	0.0930	5.550	24.750	54.500

Y: Transverse

Comfort Fatigue Health

(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	0.3100	0.3100	0.717	5.150	13.117
1.98	0.3000	0.3000	0.783	5.400	13.683
1.24	0.2700	0.2700	0.967	6.267	15.617
1.04	0.2400	0.2400	1.250	7.367	18.117
2.56	0.2000	0.1563	2.550	13.000	30.300

Z: Vertical

Comfort Fatigue Health

(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.4300	0.3029	1.500	8.500	20.550
1.52	0.4500	0.2772	1.733	9.550	22.867
2.56	0.2800	0.2240	2.450	12.633	29.500
1.24	0.3700	0.2057	2.817	14.083	32.550
3.22	0.2000	0.1794	3.467	16.750	38.117

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary

Fatigue ... Fatigue-decreased proficiency boundary

Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-14 Passenger

19-AUG-93 8:22:04

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Cross country #2
4: Position:..... Passenger
5: Speed:..... 10 mph
6: Note:..... Loaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.4600	0.3595	0.533	4.150	10.833
3.22	0.5700	0.3543	0.550	4.233	11.033
1.98	0.2400	0.2400	1.250	7.367	18.117
6.35	0.7400	0.2329	1.317	7.683	18.800
7.95	0.8000	0.2012	1.683	9.367	22.433

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	0.4500	0.4500	0.300	2.950	8.017
1.98	0.4400	0.4400	0.317	3.050	8.267
1.24	0.3800	0.3800	0.517	3.817	10.067
1.04	0.3600	0.3600	0.533	4.133	10.800
2.56	0.3100	0.2423	1.233	7.283	17.867

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.3900	0.2747	1.767	9.683	23.117
2.56	0.3100	0.2480	2.083	11.083	26.117
3.22	0.2500	0.2242	2.450	12.617	29.433
1.52	0.3400	0.2095	2.733	13.750	31.867
7.95	0.2000	0.2000	2.933	14.583	33.617

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary

Fatigue ... Fatigue-decreased proficiency boundary

Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-14 Driver

19-AUG-93 8:22:04

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Cross country #2
4: Position:..... Driver
5: Speed:..... 10 mph
6: Note:..... Loaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.2900	0.2266	1.383	7.967	19.433
3.22	0.3600	0.2238	1.417	8.117	19.717
1.98	0.1400	0.1400	3.033	14.967	34.433
6.35	0.3500	0.1102	4.350	20.183	45.250
7.95	0.4000	0.1006	4.967	22.500	50.000

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	0.2600	0.2600	1.083	6.600	16.367
1.98	0.2500	0.2500	1.167	6.967	17.217
1.24	0.2300	0.2300	1.350	7.817	19.050
1.04	0.2100	0.2100	1.567	8.833	21.300
2.56	0.1500	0.1172	3.967	18.683	42.117

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.3800	0.2677	1.833	10.000	23.867
1.52	0.3600	0.2218	2.500	12.800	29.800
2.56	0.2600	0.2080	2.767	13.900	32.117
3.22	0.2000	0.1794	3.467	16.750	38.117
5.12	0.1700	0.1700	3.767	17.867	40.500

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary

Fatigue ... Fatigue-decreased proficiency boundary

Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-15 Passenger

19-AUG-93 8:22:05

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Cross country #2
4: Position:..... Passenger
5: Speed:..... 8 mph
6: Note:..... Loaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.5000	0.3908	0.467	3.667	9.700
3.22	0.5300	0.3294	0.633	4.717	12.117
1.98	0.2800	0.2800	0.900	5.950	14.933
1.52	0.1600	0.1600	2.450	12.617	29.500
7.95	0.5000	0.1257	3.567	17.117	38.933

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	0.4800	0.4800	0.250	2.667	7.350
1.98	0.4600	0.4600	0.283	2.850	7.783
1.24	0.3400	0.3400	0.600	4.500	11.650
1.04	0.3400	0.3400	0.600	4.500	11.650
2.56	0.2800	0.2188	1.467	8.367	20.250

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.4000	0.2818	1.683	9.350	22.433
2.56	0.3500	0.2800	1.700	9.433	22.617
3.22	0.2600	0.2332	2.300	12.000	28.117
5.12	0.2200	0.2200	2.533	12.933	30.117
7.95	0.1900	0.1900	3.183	15.583	35.683

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-15 Driver

19-AUG-93 8:22:05

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Cross country #2
4: Position:..... Driver
5: Speed:..... 8 mph
6: Note:..... Loaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.2800	0.2188	1.467	8.367	20.250
3.22	0.2900	0.1803	2.033	10.833	25.617
1.98	0.1800	0.1800	2.033	10.833	25.650
1.52	0.0900	0.0900	5.817	25.750	56.617
5.12	0.2100	0.0821	6.617	28.683	62.617

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.3100	0.3100	0.717	5.150	13.117
1.52	0.2800	0.2800	0.900	5.950	14.933
1.24	0.1900	0.1900	1.867	10.083	24.050
1.04	0.1800	0.1800	2.033	10.833	25.650
2.56	0.1600	0.1250	3.600	17.250	39.183

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.3500	0.2465	2.100	11.150	26.300
2.56	0.3000	0.2400	2.200	11.550	27.183
3.22	0.2200	0.1973	3.000	14.833	34.183
5.12	0.1900	0.1900	3.183	15.583	35.683
1.52	0.2700	0.1663	3.883	18.367	41.500

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-16 Passenger

19-AUG-93 8:22:05

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Cross country #2
4: Position:..... Passenger
5: Speed:..... 6 mph
6: Note:..... Loaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.3600	0.3600	0.533	4.133	10.800
1.52	0.2400	0.2400	1.250	7.367	18.117
2.56	0.3000	0.2345	1.300	7.617	18.617
3.22	0.3400	0.2113	1.550	8.750	21.150
4.07	0.2200	0.1081	4.467	20.617	46.250

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	0.5800	0.5800	0.183	1.967	5.650
1.98	0.4900	0.4900	0.250	2.583	7.150
1.24	0.3500	0.3500	0.567	4.317	11.217
1.04	0.2600	0.2600	1.083	6.600	16.367
2.56	0.2100	0.1641	2.367	12.217	28.617

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.4000	0.2818	1.683	9.350	22.433
2.56	0.3000	0.2400	2.200	11.550	27.183
3.22	0.2300	0.2063	2.800	14.050	32.433
1.52	0.2800	0.1725	3.683	17.550	39.867
7.95	0.1700	0.1700	3.767	17.867	40.500

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-16 Driver

19-AUG-93 8:22:05

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Cross country #2
4: Position:..... Driver
5: Speed:..... 6 mph
6: Note:..... Loaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.2200	0.2200	1.450	8.300	20.117
2.56	0.1800	0.1407	3.000	14.867	34.250
3.22	0.2100	0.1305	3.367	16.367	37.300
1.52	0.1300	0.1300	3.400	16.433	37.500
4.07	0.1500	0.0737	7.683	32.500	70.250

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	0.3500	0.3500	0.567	4.317	11.217
1.98	0.3000	0.3000	0.783	5.400	13.683
1.24	0.2100	0.2100	1.567	8.833	21.300
1.04	0.1600	0.1600	2.450	12.617	29.500
2.56	0.1200	0.0938	5.483	24.500	54.117

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.4100	0.2888	1.617	9.050	21.800
2.56	0.2600	0.2080	2.767	13.900	32.117
1.52	0.3000	0.1848	3.317	16.117	36.867
3.22	0.1900	0.1704	3.750	17.833	40.367
7.95	0.1100	0.1100	7.033	30.183	65.617

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-17 Passenger

19-AUG-93 8:22:06

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Cross country #2
4: Position:..... Passenger
5: Speed:..... 12 mph
6: Note:..... Unloaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal					
			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.9900	0.6154	0.133	1.783	5.183
4.07	0.7900	0.3880	0.483	3.700	9.800
1.98	0.3700	0.3700	0.517	3.967	10.433
2.56	0.4600	0.3595	0.533	4.150	10.833
1.52	0.3400	0.3400	0.600	4.500	11.650

Y: Transverse					
			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.04	0.5700	0.5700	0.183	2.033	5.783
1.24	0.4800	0.4800	0.250	2.667	7.350
1.52	0.4700	0.4700	0.267	2.767	7.567
1.98	0.4600	0.4600	0.283	2.850	7.783
2.56	0.4300	0.3360	0.617	4.583	11.833

Z: Vertical					
			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.5100	0.3592	1.100	6.717	16.650
3.22	0.3900	0.3498	1.167	6.967	17.217
1.52	0.5500	0.3388	1.233	7.283	17.900
7.95	0.2900	0.2900	1.617	9.000	21.683
2.56	0.3500	0.2800	1.700	9.433	22.617

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-17 Driver

19-AUG-93 8:22:06

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Cross country #2
4: Position:..... Driver
5: Speed:..... 12 mph
6: Note:..... Unloaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.5800	0.3605	0.533	4.133	10.800
2.56	0.2900	0.2266	1.383	7.967	19.433
1.98	0.2200	0.2200	1.450	8.300	20.117
4.07	0.4300	0.2112	1.550	8.767	21.183
1.52	0.1600	0.1600	2.450	12.617	29.500

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.04	0.3200	0.3200	0.683	4.917	12.583
1.52	0.2700	0.2700	0.967	6.267	15.617
1.24	0.2700	0.2700	0.967	6.267	15.617
1.98	0.2600	0.2600	1.083	6.600	16.367
7.95	0.7300	0.1836	1.967	10.567	25.050

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.5300	0.3733	1.000	6.367	15.867
1.52	0.5800	0.3573	1.117	6.767	16.750
3.22	0.3700	0.3318	1.267	7.500	18.367
4.07	0.2700	0.2700	1.817	9.900	23.617
2.56	0.3100	0.2480	2.083	11.083	26.117

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUM-18 Passenger

19-AUG-93 8:22:06

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Cross country #2
4: Position:..... Passenger
5: Speed:..... 10 mph
6: Note:..... Unloaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.6500	0.4040	0.417	3.483	9.267
1.98	0.3400	0.3400	0.600	4.500	11.650
2.56	0.4200	0.3282	0.650	4.733	12.183
1.52	0.2400	0.2400	1.250	7.367	18.117
4.07	0.4700	0.2309	1.333	7.767	19.000

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	0.4900	0.4900	0.250	2.583	7.150
1.98	0.4700	0.4700	0.267	2.767	7.567
1.04	0.4700	0.4700	0.267	2.767	7.567
1.24	0.4100	0.4100	0.383	3.400	9.100
2.56	0.3700	0.2892	0.833	5.683	14.333

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.3600	0.2880	1.633	9.083	21.867
7.95	0.2800	0.2800	1.700	9.433	22.617
1.98	0.3900	0.2747	1.767	9.683	23.117
3.22	0.2700	0.2422	2.167	11.417	26.867
1.52	0.3500	0.2156	2.617	13.250	30.800

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-18 Driver

19-AUG-93 8:22:06

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Cross country #2
4: Position:..... Driver
5: Speed:..... 10 mph
6: Note:..... Unloaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.3600	0.2238	1.417	8.117	19.717
2.56	0.2500	0.1954	1.767	9.733	23.250
1.98	0.1900	0.1900	1.867	10.083	24.050
4.07	0.2300	0.1130	4.183	19.550	44.000
1.52	0.1100	0.1100	4.350	20.183	45.250

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	0.2900	0.2900	0.833	5.667	14.267
1.04	0.2900	0.2900	0.833	5.667	14.267
1.24	0.2600	0.2600	1.083	6.600	16.367
1.98	0.2400	0.2400	1.250	7.367	18.117
7.95	0.6300	0.1584	2.500	12.800	29.800

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.3300	0.2640	1.883	10.200	24.250
1.98	0.3700	0.2606	1.917	10.367	24.617
3.22	0.2700	0.2422	2.167	11.417	26.867
1.52	0.3700	0.2279	2.383	12.350	28.867
4.07	0.1800	0.1800	3.450	16.650	38.000

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-19 Passenger

19-AUG-93 8:22:07

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Cross country #2
4: Position:..... Passenger
5: Speed:..... 8 mph
6: Note:..... Unloaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)** **Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.3200	0.3200	0.683	4.917	12.583
2.56	0.3900	0.3048	0.750	5.267	13.400
3.22	0.3500	0.2176	1.483	8.433	20.433
1.52	0.2100	0.2100	1.567	8.833	21.300
4.07	0.2900	0.1424	2.950	14.650	33.750

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.4800	0.4800	0.250	2.667	7.350
1.52	0.4800	0.4800	0.250	2.667	7.350
1.04	0.3800	0.3800	0.517	3.817	10.067
1.24	0.3400	0.3400	0.600	4.500	11.650
2.56	0.2900	0.2266	1.383	7.967	19.433

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.3600	0.2880	1.633	9.083	21.867
1.98	0.4000	0.2818	1.683	9.350	22.433
7.95	0.2400	0.2400	2.200	11.550	27.183
3.22	0.2500	0.2242	2.450	12.617	29.433
4.07	0.1800	0.1800	3.450	16.650	38.000

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-19 Driver

19-AUG-93 8:22:07

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Cross country #2
4: Position:..... Driver
5: Speed:..... 8 mph
6: Note:..... Unloaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.2400	0.1876	1.900	10.267	24.433
1.98	0.1600	0.1600	2.450	12.617	29.500
3.22	0.2400	0.1492	2.750	13.800	32.000
4.07	0.2100	0.1031	4.783	21.833	48.617
1.52	0.0900	0.0900	5.817	25.750	56.617

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	0.2900	0.2900	0.833	5.667	14.267
1.98	0.2700	0.2700	0.967	6.267	15.617
1.04	0.2300	0.2300	1.350	7.817	19.050
1.24	0.2100	0.2100	1.567	8.833	21.300
7.95	0.5100	0.1282	3.467	16.717	38.050

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.3500	0.2465	2.100	11.150	26.300
2.56	0.3000	0.2400	2.200	11.550	27.183
3.22	0.1900	0.1704	3.750	17.833	40.367
1.52	0.2600	0.1602	4.117	19.250	43.367
4.07	0.1500	0.1500	4.533	20.867	46.617

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary

Fatigue ... Fatigue-decreased proficiency boundary

Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-20 Passenger

19-AUG-93 8:22:07

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Cross country #2
4: Position:..... Passenger
5: Speed:..... 6 mph
6: Note:..... Unloaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal

Comfort Fatigue Health

(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.3100	0.3100	0.717	5.150	13.117
3.22	0.3700	0.2300	1.350	7.817	19.083
4.07	0.4600	0.2259	1.383	8.000	19.500
2.56	0.2800	0.2188	1.467	8.367	20.250
1.52	0.1600	0.1600	2.450	12.617	29.500

Y: Transverse

Comfort Fatigue Health

(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	0.5000	0.5000	0.233	2.500	6.950
1.98	0.4000	0.4000	0.417	3.533	9.400
1.24	0.3500	0.3500	0.567	4.317	11.217
1.04	0.2800	0.2800	0.900	5.950	14.933
4.07	0.5300	0.2603	1.083	6.583	16.367

Z: Vertical

Comfort Fatigue Health

(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.3500	0.2800	1.700	9.433	22.617
1.98	0.3700	0.2606	1.917	10.367	24.617
3.22	0.2600	0.2332	2.300	12.000	28.117
7.95	0.2100	0.2100	2.717	13.717	31.750
4.07	0.1900	0.1900	3.183	15.583	35.683

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary

Fatigue ... Fatigue-decreased proficiency boundary

Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-20 Driver

19-AUG-93 8:22:07

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Cross country #2
4: Position:..... Driver
5: Speed:..... 6 mph
6: Note:..... Unloaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.1500	0.1500	2.717	13.717	31.750
3.22	0.2400	0.1492	2.750	13.800	32.000
4.07	0.2700	0.1326	3.283	16.017	36.617
2.56	0.1500	0.1172	3.967	18.683	42.117
1.52	0.0800	0.0800	6.850	29.550	64.367

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	0.3000	0.3000	0.783	5.400	13.683
1.24	0.2200	0.2200	1.450	8.300	20.117
1.98	0.2100	0.2100	1.567	8.833	21.300
1.04	0.1700	0.1700	2.233	11.683	27.433
4.07	0.2100	0.1031	4.783	21.833	48.617

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.3200	0.2254	2.433	12.517	29.250
2.56	0.2800	0.2240	2.450	12.633	29.500
3.22	0.1800	0.1614	4.067	19.050	43.000
4.07	0.1600	0.1600	4.117	19.267	43.367
1.52	0.2500	0.1540	4.350	20.183	45.250

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-21 Passenger

19-AUG-93 8:22:08

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Cross country #2
4: Position:..... Passenger
5: Speed:..... 12 mph
6: Note:..... Bobtail

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal

Comfort Fatigue Health

(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.4900	0.4900	0.250	2.583	7.150
2.56	0.5900	0.4611	0.283	2.850	7.767
3.22	0.6900	0.4289	0.333	3.183	8.567
4.07	0.8000	0.3929	0.450	3.633	9.617
1.52	0.3400	0.3400	0.600	4.500	11.650

Y: Transverse

Comfort Fatigue Health

(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.24	0.5900	0.5900	0.183	1.917	5.500
1.04	0.5700	0.5700	0.183	2.033	5.783
1.52	0.5400	0.5400	0.200	2.217	6.250
1.98	0.4200	0.4200	0.367	3.283	8.800
3.22	0.6600	0.4102	0.383	3.400	9.083

Z: Vertical

Comfort Fatigue Health

(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.4800	0.3381	1.233	7.300	17.967
2.56	0.4000	0.3199	1.367	7.883	19.217
3.22	0.3200	0.2870	1.633	9.117	21.933
7.95	0.2800	0.2800	1.700	9.433	22.617
4.07	0.2700	0.2700	1.817	9.900	23.617

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary

Fatigue ... Fatigue-decreased proficiency boundary

Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-21 Driver

19-AUG-93 8:22:08

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Cross country #2
4: Position:..... Driver
5: Speed:..... 12 mph
6: Note:..... Bobtail

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.4200	0.2611	1.067	6.567	16.300
1.98	0.2600	0.2600	1.083	6.600	16.367
2.56	0.3200	0.2501	1.167	6.967	17.183
4.07	0.4400	0.2161	1.500	8.500	20.583
1.52	0.1600	0.1600	2.450	12.617	29.500

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.24	0.3300	0.3300	0.633	4.700	12.117
1.04	0.3200	0.3200	0.683	4.917	12.583
1.52	0.3100	0.3100	0.717	5.150	13.117
1.98	0.2400	0.2400	1.250	7.367	18.117
7.95	0.8100	0.2037	1.650	9.217	22.117

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.4600	0.3240	1.333	7.750	18.933
1.52	0.4500	0.2772	1.733	9.550	22.867
4.07	0.2700	0.2700	1.817	9.900	23.617
2.56	0.3200	0.2560	1.983	10.617	25.183
3.22	0.2800	0.2511	2.050	10.900	25.750

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-22 Passenger

19-AUG-93 8:22:08

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Cross country #2
4: Position:..... Passenger
5: Speed:..... 10 mph
6: Note:..... Bobtail

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.4000	0.4000	0.417	3.533	9.400
2.56	0.5100	0.3986	0.433	3.550	9.450
3.22	0.4900	0.3046	0.750	5.283	13.400
4.07	0.6000	0.2947	0.800	5.533	14.000
1.52	0.2800	0.2800	0.900	5.950	14.933

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	0.4800	0.4800	0.250	2.667	7.350
1.04	0.4800	0.4800	0.250	2.667	7.350
1.24	0.4700	0.4700	0.267	2.767	7.567
1.98	0.4400	0.4400	0.317	3.050	8.267
2.56	0.4100	0.3204	0.683	4.917	12.583

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.4100	0.3279	1.300	7.617	18.650
1.98	0.4000	0.2818	1.683	9.350	22.433
3.22	0.3000	0.2621	1.817	9.933	23.717
7.95	0.2600	0.2600	1.933	10.400	24.683
4.07	0.2300	0.2300	2.350	12.217	28.550

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-22 Driver

19-AUG-93 8:22:08

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Cross country #2
4: Position:..... Driver
5: Speed:..... 10 mph
6: Note:..... Bobtail

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.2400	0.2400	1.250	7.367	18.117
2.56	0.3000	0.2345	1.300	7.617	18.617
3.22	0.3300	0.2051	1.633	9.117	21.933
4.07	0.3500	0.1719	2.183	11.500	27.117
1.52	0.1400	0.1400	3.033	14.967	34.433

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	0.2900	0.2900	0.833	5.667	14.267
1.24	0.2800	0.2800	0.900	5.950	14.933
1.04	0.2800	0.2800	0.900	5.950	14.933
1.98	0.2400	0.2400	1.250	7.367	18.117
7.95	0.7300	0.1836	1.967	10.567	25.050

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.3900	0.2747	1.767	9.683	23.117
2.56	0.3400	0.2720	1.800	9.800	23.433
1.52	0.3600	0.2218	2.500	12.800	29.800
4.07	0.2200	0.2200	2.533	12.933	30.117
3.22	0.2400	0.2153	2.617	13.300	30.867

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-23 Passenger

19-AUG-93 8:22:09

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Cross country #2
4: Position:..... Passenger
5: Speed:..... 8 mph
6: Note:..... Bobtail

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.3900	0.3900	0.467	3.667	9.717
2.56	0.4100	0.3204	0.683	4.917	12.583
4.07	0.5700	0.2800	0.900	5.950	14.933
1.52	0.2400	0.2400	1.250	7.367	18.117
5.12	0.5500	0.2149	1.517	8.567	20.717

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	0.4400	0.4400	0.317	3.050	8.267
1.98	0.4300	0.4300	0.333	3.167	8.533
1.04	0.4100	0.4100	0.383	3.400	9.100
1.24	0.4000	0.4000	0.417	3.533	9.400
7.95	1.2300	0.3093	0.733	5.167	13.150

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.4000	0.2818	1.683	9.350	22.433
2.56	0.3500	0.2800	1.700	9.433	22.617
7.95	0.2600	0.2600	1.933	10.400	24.683
3.22	0.2600	0.2332	2.300	12.000	28.117
5.12	0.2000	0.2000	2.933	14.583	33.617

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-23 Driver

19-AUG-93 8:22:09

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Cross country #2
4: Position:..... Driver
5: Speed:..... 8 mph
6: Note:..... Bobtail

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.2100	0.2100	1.567	8.833	21.300
2.56	0.2400	0.1876	1.900	10.267	24.433
4.07	0.3100	0.1523	2.650	13.467	31.250
3.22	0.2400	0.1492	2.750	13.800	32.000
1.52	0.1300	0.1300	3.400	16.433	37.500

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	0.2700	0.2700	0.967	6.267	15.617
1.98	0.2500	0.2500	1.167	6.967	17.217
1.24	0.2400	0.2400	1.250	7.367	18.117
1.04	0.2400	0.2400	1.250	7.367	18.117
7.95	0.7400	0.1861	1.917	10.367	24.650

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.3900	0.2747	1.767	9.683	23.117
2.56	0.3100	0.2480	2.083	11.083	26.117
1.52	0.3100	0.1910	3.150	15.467	35.500
4.07	0.1900	0.1900	3.183	15.583	35.683
3.22	0.2000	0.1794	3.467	16.750	38.117

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-24 Passenger

19-AUG-93 8:22:09

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Cross country #2
4: Position:..... Passenger
5: Speed:..... 6 mph
6: Note:..... Bobtail

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.4100	0.4100	0.383	3.400	9.100
4.07	0.7200	0.3537	0.550	4.250	11.050
2.56	0.4100	0.3204	0.683	4.917	12.583
1.52	0.2400	0.2400	1.250	7.367	18.117
3.22	0.3800	0.2362	1.283	7.533	18.467

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.5100	0.5100	0.233	2.433	6.750
1.52	0.4900	0.4900	0.250	2.583	7.150
1.24	0.3300	0.3300	0.633	4.700	12.117
1.04	0.3000	0.3000	0.783	5.400	13.683
4.07	0.5400	0.2652	1.050	6.417	16.000

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.4200	0.2958	1.550	8.767	21.150
2.56	0.3500	0.2800	1.700	9.433	22.617
4.07	0.2300	0.2300	2.350	12.217	28.550
3.22	0.2400	0.2153	2.617	13.300	30.867
7.95	0.2000	0.2000	2.933	14.583	33.617

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-24 Driver

19-AUG-93 8:22:09

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Cross country #2
4: Position:..... Driver
5: Speed:..... 6 mph
6: Note:..... Bobtail

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.2300	0.2300	1.350	7.817	19.050
4.07	0.3700	0.1817	2.000	10.717	25.367
2.56	0.2300	0.1797	2.033	10.867	25.683
1.52	0.1400	0.1400	3.033	14.967	34.433
3.22	0.2100	0.1305	3.367	16.367	37.300

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.52	0.3000	0.3000	0.783	5.400	13.683
1.98	0.2700	0.2700	0.967	6.267	15.617
1.24	0.2200	0.2200	1.450	8.300	20.117
1.04	0.2000	0.2000	1.700	9.433	22.617
7.95	0.5400	0.1358	3.167	15.550	35.683

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.3600	0.2536	2.017	10.750	25.433
4.07	0.2400	0.2400	2.200	11.550	27.183
2.56	0.2900	0.2320	2.317	12.083	28.300
3.22	0.1900	0.1704	3.750	17.833	40.367
1.52	0.2300	0.1417	4.917	22.367	49.750

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-25 Passenger

19-AUG-93 8:22:10

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Paved
4: Position:..... Passenger
5: Speed:..... 25 mph
6: Note:..... Bobtail

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
5.12	0.3900	0.1524	2.650	13.433	31.183
2.56	0.1500	0.1172	3.967	18.683	42.117
3.22	0.1500	0.0932	5.533	24.683	54.433
1.98	0.0500	0.0500	12.833	50.500	105.750
4.07	0.0800	0.0393	17.367	65.750	135.250

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
10.04	0.4100	0.0817	6.667	28.867	62.867
3.22	0.1100	0.0684	8.500	35.500	76.250
7.95	0.2500	0.0629	9.500	39.050	83.250
2.56	0.0700	0.0547	11.417	45.683	96.367
1.98	0.0500	0.0500	12.833	50.500	105.750

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.2700	0.2422	2.167	11.417	26.867
2.56	0.2600	0.2080	2.767	13.900	32.117
5.12	0.1500	0.1500	4.533	20.867	46.617
10.04	0.1400	0.1116	6.900	29.683	64.617
7.95	0.1100	0.1100	7.033	30.183	65.617

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary

Fatigue ... Fatigue-decreased proficiency boundary

Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-25 Driver

19-AUG-93 8:22:10

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Paved
4: Position:..... Driver
5: Speed:..... 25 mph
6: Note:..... Bobtail

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
5.12	0.2200	0.0860	6.200	27.183	59.500
3.22	0.0800	0.0497	12.900	50.867	106.500
2.56	0.0600	0.0469	13.933	54.250	113.000
4.07	0.0500	0.0246	30.617	108.000	215.500
6.35	0.0700	0.0220	34.750	120.750	239.500

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
10.04	0.2300	0.0458	14.333	55.617	115.750
3.22	0.0700	0.0435	15.300	58.867	122.000
7.95	0.1400	0.0352	19.900	74.000	151.250
2.56	0.0400	0.0313	23.000	84.000	170.000
1.98	0.0300	0.0300	24.150	87.750	177.250

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.2600	0.2332	2.300	12.000	28.117
2.56	0.2400	0.1920	3.133	15.367	35.250
5.12	0.1400	0.1400	5.000	22.683	50.367
7.95	0.0900	0.0900	9.217	38.050	81.250
10.04	0.1000	0.0797	10.833	43.683	92.500

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary

Fatigue ... Fatigue-decreased proficiency boundary

Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-26 Passenger

19-AUG-93 8:22:10

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Paved
4: Position:..... Passenger
5: Speed:..... 35 mph
6: Note:..... Bobtail

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.2300	0.1797	2.033	10.867	25.683
3.22	0.2200	0.1367	3.133	15.433	35.367
4.07	0.2700	0.1326	3.283	16.017	36.617
1.98	0.0900	0.0900	5.817	25.750	56.617
7.95	0.2500	0.0629	9.500	39.050	83.250

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
4.07	0.2900	0.1424	2.950	14.650	33.750
10.04	0.6100	0.1215	3.750	17.867	40.500
7.95	0.4800	0.1207	3.800	18.000	40.750
20.17	0.7900	0.0783	7.067	30.300	65.867
3.22	0.1200	0.0746	7.550	32.050	69.367

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.3500	0.2800	1.700	9.433	22.617
3.22	0.3000	0.2691	1.817	9.933	23.717
7.95	0.1900	0.1900	3.183	15.583	35.683
4.07	0.1400	0.1400	5.000	22.683	50.367
10.04	0.1600	0.1275	5.717	25.367	55.867

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary

Fatigue ... Fatigue-decreased proficiency boundary

Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-26 Driver

19-AUG-93 8:22:10

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Paved
4: Position:..... Driver
5: Speed:..... 35 mph
6: Note:..... Bobtail

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.1100	0.0860	6.200	27.183	59.500
3.22	0.1000	0.0622	9.650	39.550	84.250
4.07	0.1200	0.0589	10.367	42.000	89.117
1.98	0.0500	0.0500	12.833	50.500	105.750
7.95	0.1200	0.0302	24.000	87.250	176.250

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
4.07	0.1500	0.0737	7.683	32.500	70.250
10.04	0.3500	0.0697	8.267	34.683	74.617
7.95	0.2600	0.0654	9.017	37.367	79.867
3.22	0.0700	0.0435	15.300	58.867	122.000
2.56	0.0500	0.0391	17.500	66.117	136.000

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.3200	0.2560	1.983	10.617	25.183
3.22	0.2800	0.2511	2.050	10.900	25.750
7.95	0.1500	0.1500	4.533	20.867	46.617
4.07	0.1300	0.1300	5.567	24.800	54.617
10.04	0.1000	0.0797	10.833	43.683	92.500

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-27 Passenger

19-AUG-93 8:22:10

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Paved
4: Position:..... Passenger
5: Speed:..... 45 mph
6: Note:..... Bobtail

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.2300	0.1797	2.033	10.867	25.683
3.22	0.2100	0.1305	3.367	16.367	37.300
5.12	0.2800	0.1094	4.383	20.333	45.617
1.98	0.1000	0.1000	5.000	22.683	50.367
4.07	0.1500	0.0737	7.683	32.500	70.250

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
25.40	1.2300	0.0969	5.233	23.550	52.250
4.07	0.1900	0.0933	5.517	24.617	54.367
5.12	0.2300	0.0899	5.833	25.750	56.617
10.04	0.4300	0.0857	6.233	27.250	59.750
7.95	0.3300	0.0830	6.517	28.300	61.867

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.2900	0.2601	1.933	10.400	24.683
2.56	0.3100	0.2480	2.083	11.083	26.117
7.95	0.1600	0.1600	4.117	19.267	43.367
5.12	0.1500	0.1500	4.533	20.867	46.617
10.04	0.1300	0.1036	7.633	32.367	70.000

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-27 Driver

19-AUG-93 8:22:10

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Paved
4: Position:..... Driver
5: Speed:..... 45 mph
6: Note:..... Bobtail

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
5.12	0.1900	0.0742	7.600	32.250	69.750
2.56	0.0900	0.0703	8.183	34.367	73.867
3.22	0.0900	0.0559	11.083	44.550	94.117
4.07	0.0900	0.0442	15.000	57.867	120.000
1.98	0.0400	0.0400	17.000	64.500	133.000

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
4.07	0.1000	0.0491	13.117	51.500	107.750
10.04	0.2400	0.0478	13.583	53.117	110.750
5.12	0.1200	0.0469	13.933	54.250	113.000
7.95	0.1800	0.0453	14.550	56.367	117.250
3.22	0.0700	0.0435	15.300	58.867	122.000

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.3200	0.2560	1.983	10.617	25.183
3.22	0.2700	0.2422	2.167	11.417	26.867
7.95	0.1600	0.1600	4.117	19.267	43.367
5.12	0.1300	0.1300	5.567	24.800	54.617
10.04	0.1100	0.0877	9.550	39.250	83.617

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-28 Passenger

19-AUG-93 8:22:11

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Paved
4: Position:..... Passenger
5: Speed:..... 55 mph
6: Note:..... Bobtail

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.3000	0.2345	1.300	7.617	18.617
5.12	0.4000	0.1563	2.550	13.000	30.300
1.98	0.1500	0.1500	2.717	13.717	31.750
3.22	0.2100	0.1305	3.367	16.367	37.300
4.07	0.2100	0.1031	4.783	21.833	48.617

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
4.07	0.2300	0.1130	4.183	19.550	44.000
6.35	0.3100	0.0976	5.183	23.367	51.750
3.22	0.1200	0.0746	7.550	32.050	69.367
1.04	0.0600	0.0600	10.117	41.183	87.500
5.12	0.1500	0.0586	10.433	42.250	89.617

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.4400	0.3519	1.150	6.917	17.083
3.22	0.3400	0.3049	1.483	8.417	20.367
7.95	0.1800	0.1800	3.450	16.650	38.000
5.12	0.1700	0.1700	3.767	17.867	40.500
6.35	0.1600	0.1600	4.117	19.267	43.367

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary

Fatigue ... Fatigue-decreased proficiency boundary

Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-28 Driver

19-AUG-93 8:22:11

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Paved
4: Position:..... Driver
5: Speed:..... 55 mph
6: Note:..... Bobtail

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.1600	0.1250	3.600	17.250	39.183
5.12	0.3000	0.1172	3.967	18.683	42.117
1.98	0.0900	0.0900	5.817	25.750	56.617
3.22	0.1200	0.0746	7.550	32.050	69.367
4.07	0.1500	0.0737	7.683	32.500	70.250

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
4.07	0.1100	0.0540	11.617	46.367	97.617
6.35	0.1600	0.0504	12.717	50.117	105.000
3.22	0.0700	0.0435	15.300	58.867	122.000
2.56	0.0500	0.0391	17.500	66.117	136.000
10.04	0.1700	0.0339	20.867	77.117	157.000

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.4000	0.3199	1.367	7.883	19.217
3.22	0.2900	0.2601	1.933	10.400	24.683
5.12	0.1700	0.1700	3.767	17.867	40.500
7.95	0.1400	0.1400	5.000	22.683	50.367
1.98	0.1700	0.1197	6.250	27.300	59.867

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-29 Passenger

19-AUG-93 8:22:11

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Paved
4: Position:..... Passenger
5: Speed:..... 25 mph
6: Note:..... Unloaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.1500	0.1172	3.967	18.683	42.117
3.22	0.1800	0.1119	4.250	19.800	44.433
1.98	0.0500	0.0500	12.833	50.500	105.750
4.07	0.1000	0.0491	13.117	51.500	107.750
40.26	0.9800	0.0487	13.267	52.000	108.750

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
7.95	0.3400	0.0855	6.250	27.367	59.867
3.22	0.1100	0.0684	8.500	35.500	76.250
10.04	0.3300	0.0657	8.967	37.117	79.500
1.98	0.0600	0.0600	10.117	41.183	87.500
4.07	0.1000	0.0491	13.117	51.500	107.750

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.3700	0.3318	1.267	7.500	18.367
2.56	0.3300	0.2640	1.883	10.200	24.250
7.95	0.1500	0.1500	4.533	20.867	46.617
4.07	0.1000	0.1000	8.000	33.750	72.750
10.04	0.1200	0.0956	8.500	35.500	76.250

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-29 Driver

19-AUG-93 8:22:11

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Paved
4: Position:..... Driver
5: Speed:..... 25 mph
6: Note:..... Unloaded trailer

Third-octave bands with greatest
weighted RMS accelerations (m/s²)

Durations of WBV exposure
before reaching ISO limits*

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.0900	0.0559	11.083	44.550	94.117
2.56	0.0700	0.0547	11.417	45.683	96.367
4.07	0.0500	0.0246	30.617	108.000	215.500
7.95	0.0900	0.0226	33.617	117.500	233.250
20.17	0.2100	0.0208	37.050	128.000	252.500

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
7.95	0.1900	0.0478	13.583	53.117	110.867
1.98	0.0400	0.0400	17.000	64.500	133.000
10.04	0.2000	0.0398	17.083	64.750	133.500
2.56	0.0400	0.0313	23.000	84.000	170.000
3.22	0.0500	0.0311	23.150	84.500	171.000

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.3000	0.2691	1.817	9.933	23.717
2.56	0.2700	0.2160	2.600	13.250	30.750
7.95	0.1000	0.1000	8.000	33.750	72.750
1.98	0.1100	0.0775	11.250	45.117	95.250
10.04	0.0800	0.0637	14.433	56.000	116.500

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-30 Passenger

19-AUG-93 8:22:11

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Paved
4: Position:..... Passenger
5: Speed:..... 35 mph
6: Note:..... Unloaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
5.12	0.3800	0.1485	2.767	13.900	32.183
4.07	0.3000	0.1474	2.800	14.050	32.433
2.56	0.1300	0.1016	4.883	22.250	49.500
3.22	0.1500	0.0932	5.533	24.683	54.433
1.98	0.0500	0.0500	12.833	50.500	105.750

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
4.07	0.3000	0.1474	2.800	14.050	32.433
5.12	0.2900	0.1133	4.167	19.500	43.800
7.95	0.3400	0.0855	6.250	27.367	59.867
20.17	0.8200	0.0813	6.700	29.000	63.250
10.04	0.3400	0.0677	8.617	35.867	77.000

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.2500	0.2242	2.450	12.617	29.433
2.56	0.2600	0.2080	2.767	13.900	32.117
4.07	0.2000	0.2000	2.933	14.583	33.617
7.95	0.1500	0.1500	4.533	20.867	46.617
5.12	0.1300	0.1300	5.567	24.800	54.617

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-30 Driver

19-AUG-93 8:22:11

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Paved
4: Position:..... Driver
5: Speed:..... 35 mph
6: Note:..... Unloaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
5.12	0.2200	0.0860	6.200	27.183	59.500
4.07	0.1700	0.0835	6.467	28.117	61.367
2.56	0.0600	0.0469	13.933	54.250	113.000
3.22	0.0700	0.0435	15.300	58.867	122.000
1.98	0.0300	0.0300	24.150	87.750	177.250

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
4.07	0.1300	0.0639	9.300	38.367	82.000
7.95	0.2000	0.0503	12.717	50.183	105.250
20.17	0.4400	0.0436	15.250	58.750	121.750
10.04	0.2000	0.0398	17.083	64.750	133.500
5.12	0.0900	0.0352	19.933	74.117	151.250

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.2100	0.1883	3.217	15.750	36.050
2.56	0.2200	0.1760	3.567	17.117	38.933
5.12	0.1400	0.1400	5.000	22.683	50.367
4.07	0.1100	0.1100	7.033	30.183	65.617
7.95	0.0900	0.0900	9.217	38.050	81.250

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUM-31 Passenger

19-AUG-93 8:22:12

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Paved
4: Position:..... Passenger
5: Speed:..... 45 mph
6: Note:..... Unloaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.1900	0.1485	2.767	13.900	32.183
4.07	0.3000	0.1474	2.800	14.050	32.433
3.22	0.1800	0.1119	4.250	19.800	44.433
1.98	0.0900	0.0900	5.817	25.750	56.617
7.95	0.2400	0.0604	10.033	40.867	87.000

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
4.07	0.2100	0.1031	4.783	21.833	48.617
3.22	0.1300	0.0808	6.767	29.183	63.617
5.12	0.1900	0.0742	7.600	32.250	69.750
25.40	0.8800	0.0693	8.350	34.933	75.117
7.95	0.2700	0.0679	8.583	35.750	76.750

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.3700	0.2960	1.550	8.750	21.117
3.22	0.3000	0.2691	1.817	9.933	23.717
4.07	0.1800	0.1800	3.450	16.650	38.000
10.04	0.1700	0.1355	5.250	23.617	52.250
7.95	0.1200	0.1200	6.233	27.250	59.750

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-31 Driver

19-AUG-93 8:22:12

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Paved
4: Position:..... Driver
5: Speed:..... 45 mph
6: Note:..... Unloaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
4.07	0.1600	0.0786	7.033	30.183	65.617
2.56	0.1000	0.0782	7.083	30.367	66.000
3.22	0.1000	0.0622	9.650	39.550	84.250
1.98	0.0600	0.0600	10.117	41.183	87.500
5.12	0.0800	0.0313	23.000	84.000	170.000

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
4.07	0.0900	0.0442	15.000	57.867	120.000
7.95	0.1700	0.0427	15.650	60.000	124.250
2.56	0.0500	0.0391	17.500	66.117	136.000
3.22	0.0600	0.0373	18.550	69.500	142.750
25.40	0.4200	0.0331	21.500	79.117	161.000

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.3000	0.2400	2.200	11.550	27.183
3.22	0.2300	0.2063	2.800	14.050	32.433
4.07	0.1100	0.1100	7.033	30.183	65.617
7.95	0.0900	0.0900	9.217	38.050	81.250
1.98	0.1100	0.0775	11.250	45.117	95.250

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-32 Passenger

19-AUG-93 8:22:12

1: Vehicle:..... M916 ride quality
2: Date:..... August 25 , 1992
3: Course:..... Paved
4: Position:..... Passenger
5: Speed:..... 55 mph
6: Note:..... Unloaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)** **Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.1800	0.1407	3.000	14.867	34.250
4.07	0.2700	0.1326	3.283	16.017	36.617
3.22	0.1500	0.0932	5.533	24.683	54.433
1.98	0.0900	0.0900	5.817	25.750	56.617
7.95	0.3100	0.0780	7.100	30.500	66.117

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
7.95	0.4400	0.1106	4.317	20.050	45.000
4.07	0.2200	0.1081	4.467	20.617	46.250
6.35	0.2900	0.0913	5.700	25.300	55.750
3.22	0.1400	0.0870	6.100	26.750	58.750
2.56	0.0900	0.0703	8.183	34.367	73.867

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.3400	0.2720	1.800	9.800	23.433
3.22	0.2800	0.2511	2.050	10.900	25.750
7.95	0.2200	0.2200	2.533	12.933	30.117
4.07	0.1600	0.1600	4.117	19.267	43.367
6.35	0.1500	0.1500	4.533	20.867	46.617

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-32 Driver

19-AUG-93 8:22:12

1: Vehicle:..... M916 ride quality
2: Date:..... August 25 , 1992
3: Course:..... Paved
4: Position:..... Driver
5: Speed:..... 55 mph
6: Note:..... Unloaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.1000	0.0782	7.083	30.367	66.000
4.07	0.1300	0.0639	9.300	38.367	82.000
3.22	0.0900	0.0559	11.083	44.550	94.117
1.98	0.0500	0.0500	12.833	50.500	105.750
31.92	0.7100	0.0445	14.867	57.500	119.250

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
7.95	0.2700	0.0679	8.583	35.750	76.750
4.07	0.1000	0.0491	13.117	51.500	107.750
6.35	0.1500	0.0472	13.800	53.867	112.250
3.22	0.0600	0.0373	18.550	69.500	142.750
2.56	0.0400	0.0313	23.000	84.000	170.000

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.2700	0.2160	2.600	13.250	30.750
3.22	0.2000	0.1794	3.467	16.750	38.117
7.95	0.1200	0.1200	6.233	27.250	59.750
4.07	0.0900	0.0900	9.217	38.050	81.250
1.98	0.1100	0.0775	11.250	45.117	95.250

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary

Fatigue ... Fatigue-decreased proficiency boundary

Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-33 Passenger

19-AUG-93 8:22:13

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Paved
4: Position:..... Passenger
5: Speed:..... 25 mph
6: Note:..... Loaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.3200	0.1989	1.717	9.500	22.750
2.56	0.1500	0.1172	3.967	18.683	42.117
7.95	0.4100	0.1031	4.783	21.867	48.683
6.35	0.2200	0.0692	8.350	34.933	75.117
1.98	0.0600	0.0600	10.117	41.183	87.500

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.1100	0.0684	8.500	35.500	76.250
1.98	0.0600	0.0600	10.117	41.183	87.500
7.95	0.2300	0.0578	10.617	42.933	91.000
6.35	0.1800	0.0567	10.900	43.933	93.000
10.04	0.2700	0.0538	11.683	46.617	98.000

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.3500	0.3139	1.400	8.083	19.683
7.95	0.1700	0.1700	3.767	17.867	40.500
2.56	0.2100	0.1680	3.833	18.150	41.050
6.35	0.1300	0.1300	5.567	24.800	54.617
10.04	0.1400	0.1116	6.900	29.683	64.617

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary

Fatigue ... Fatigue-decreased proficiency boundary

Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-33 Driver

19-AUG-93 8:22:13

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Paved
4: Position:..... Driver
5: Speed:..... 25 mph
6: Note:..... Loaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.1700	0.1057	4.617	21.217	47.367
2.56	0.0900	0.0703	8.183	34.367	73.867
7.95	0.2000	0.0503	12.717	50.183	105.250
1.98	0.0500	0.0500	12.833	50.500	105.750
6.35	0.1100	0.0346	20.300	75.367	153.750

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.0500	0.0311	23.150	84.500	171.000
1.98	0.0300	0.0300	24.150	87.750	177.250
1.52	0.0300	0.0300	24.150	87.750	177.250
10.04	0.1500	0.0299	24.250	88.000	178.000
6.35	0.0800	0.0252	29.750	105.250	210.500

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.2600	0.2332	2.300	12.000	28.117
2.56	0.1700	0.1360	5.217	23.500	52.000
7.95	0.1300	0.1300	5.567	24.800	54.617
6.35	0.1100	0.1100	7.033	30.183	65.617
10.04	0.0900	0.0717	12.433	49.117	103.250

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-34 Passenger

19-AUG-93 8:22:13

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Paved
4: Position:..... Passenger
5: Speed:..... 35 mph
6: Note:..... Loaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.2200	0.1367	3.133	15.433	35.367
2.56	0.1300	0.1016	4.883	22.250	49.500
1.98	0.0800	0.0800	6.850	29.550	64.367
7.95	0.2600	0.0654	9.017	37.367	79.867
1.52	0.0500	0.0500	12.833	50.500	105.750

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
4.07	0.3000	0.1474	2.800	14.050	32.433
20.17	0.7800	0.0773	7.183	30.750	66.750
10.04	0.3400	0.0677	8.617	35.867	77.000
5.12	0.1700	0.0664	8.833	36.683	78.500
7.95	0.2400	0.0604	10.033	40.867	87.000

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.2500	0.2242	2.450	12.617	29.433
4.07	0.1800	0.1800	3.450	16.650	38.000
2.56	0.2200	0.1760	3.567	17.117	38.933
7.95	0.1300	0.1300	5.567	24.800	54.617
5.12	0.1000	0.1000	8.000	33.750	72.750

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary

Fatigue ... Fatigue-decreased proficiency boundary

Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-34 Driver

19-AUG-93 8:22:13

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Paved
4: Position:..... Driver
5: Speed:..... 35 mph
6: Note:..... Loaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.1300	0.0808	6.767	29.183	63.617
2.56	0.0900	0.0703	8.183	34.367	73.867
1.98	0.0600	0.0600	10.117	41.183	87.500
7.95	0.1300	0.0327	21.800	80.117	162.750
1.52	0.0300	0.0300	24.150	87.750	177.250

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
4.07	0.1400	0.0688	8.433	35.250	75.750
10.04	0.2100	0.0418	16.083	61.500	127.000
20.17	0.3600	0.0357	19.550	73.000	149.000
7.95	0.1400	0.0352	19.900	74.000	151.250
5.12	0.0800	0.0313	23.000	84.000	170.000

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
3.22	0.2000	0.1794	3.467	16.750	38.117
2.56	0.1900	0.1520	4.433	20.550	46.000
4.07	0.1200	0.1200	6.233	27.250	59.750
7.95	0.0900	0.0900	9.217	38.050	81.250
10.04	0.1000	0.0797	10.833	43.683	92.500

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary

Fatigue ... Fatigue-decreased proficiency boundary

Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-35 Passenger

19-AUG-93 8:22:13

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Paved
4: Position:..... Passenger
5: Speed:..... 45 mph
6: Note:..... Loaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.1500	0.1500	2.717	13.717	31.750
2.56	0.1200	0.0938	5.483	24.500	54.117
3.22	0.1400	0.0870	6.100	26.750	58.750
5.12	0.2000	0.0782	7.083	30.367	66.000
6.35	0.2400	0.0755	7.417	31.617	68.500

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
5.12	0.2600	0.1016	4.883	22.250	49.500
25.40	1.1000	0.0866	6.133	26.933	59.000
4.07	0.1400	0.0688	8.433	35.250	75.750
6.35	0.2100	0.0661	8.900	36.867	79.000
10.04	0.3100	0.0618	9.733	39.867	84.867

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
5.12	0.1800	0.1800	3.450	16.650	38.000
3.22	0.2000	0.1794	3.467	16.750	38.117
2.56	0.2200	0.1760	3.567	17.117	38.933
6.35	0.1400	0.1400	5.000	22.683	50.367
10.04	0.1400	0.1116	6.900	29.683	64.617

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary

Fatigue ... Fatigue-decreased proficiency boundary

Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-35 Driver

19-AUG-93 8:22:13

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Paved
4: Position:..... Driver
5: Speed:..... 45 mph
6: Note:..... Loaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.1100	0.1100	4.350	20.183	45.250
2.56	0.0900	0.0703	8.183	34.367	73.867
3.22	0.0900	0.0559	11.083	44.550	94.117
1.52	0.0500	0.0500	12.833	50.500	105.750
5.12	0.1200	0.0469	13.933	54.250	113.000

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
25.40	0.5000	0.0394	17.333	65.617	135.000
10.04	0.1900	0.0378	18.217	68.500	140.500
5.12	0.0900	0.0352	19.933	74.117	151.250
12.68	0.1900	0.0300	24.183	87.750	177.500
4.07	0.0600	0.0295	24.683	89.367	180.500

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.1900	0.1520	4.433	20.550	46.000
3.22	0.1500	0.1345	5.300	23.800	52.617
5.12	0.1300	0.1300	5.567	24.800	54.617
6.35	0.1200	0.1200	6.233	27.250	59.750
1.98	0.1600	0.1127	6.800	29.367	63.867

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-36 Passenger

19-AUG-93 8:22:14

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Paved
4: Position:..... Passenger
5: Speed:..... 55 mph
6: Note:..... Loaded trailer

Third-octave bands with greatest
weighted RMS accelerations (m/s²)

Durations of WBV exposure
before reaching ISO limits*

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.2100	0.2100	1.567	8.833	21.300
3.22	0.3000	0.1865	1.917	10.350	24.617
7.95	0.6600	0.1660	2.317	12.050	28.250
2.56	0.1700	0.1329	3.283	16.000	36.550
1.52	0.1000	0.1000	5.000	22.683	50.367

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
4.07	0.2200	0.1081	4.467	20.617	46.250
6.35	0.3400	0.1070	4.533	20.867	46.750
3.22	0.1500	0.0932	5.533	24.683	54.433
2.56	0.1000	0.0782	7.083	30.367	66.000
5.12	0.1700	0.0664	8.833	36.683	78.500

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.3400	0.2720	1.800	9.800	23.433
7.95	0.2200	0.2200	2.533	12.933	30.117
3.22	0.2400	0.2153	2.617	13.300	30.867
6.35	0.1800	0.1800	3.450	16.650	38.000
1.98	0.2300	0.1620	4.033	19.000	42.750

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

**USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)**

RUN-36 Driver

19-AUG-93 8:22:14

1: Vehicle:..... M916 ride quality
2: Date:..... August 25, 1992
3: Course:..... Paved
4: Position:..... Driver
5: Speed:..... 55 mph
6: Note:..... Loaded trailer

**Third-octave bands with greatest
weighted RMS accelerations (m/s²)**

**Durations of WBV exposure
before reaching ISO limits***

X: Longitudinal			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
1.98	0.1400	0.1400	3.033	14.967	34.433
3.22	0.1800	0.1119	4.250	19.800	44.433
2.56	0.1300	0.1016	4.883	22.250	49.500
7.95	0.3000	0.0754	7.433	31.683	68.500
1.52	0.0700	0.0700	8.233	34.500	74.250

Y: Transverse			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
6.35	0.1700	0.0535	11.750	46.867	98.617
4.07	0.0900	0.0442	15.000	57.867	120.000
3.22	0.0600	0.0373	18.550	69.500	142.750
2.56	0.0400	0.0313	23.000	84.000	170.000
1.98	0.0300	0.0300	24.150	87.750	177.250

Z: Vertical			Comfort	Fatigue	Health
(Hz)	actual	weighted	(hours)	(hours)	(hours)
2.56	0.2900	0.2320	2.317	12.083	28.300
3.22	0.1900	0.1704	3.750	17.833	40.367
1.98	0.2200	0.1550	4.317	20.050	45.000
7.95	0.1300	0.1300	5.567	24.800	54.617
6.35	0.1100	0.1100	7.033	30.183	65.617

* International Standards Organization ISO 2631: Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-01
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:21:57



Course: Belgian block
 Speed: 5 mph
 Note: Bobtail

HSEL: Health and safety exposure limit
 FDPB: Fatigue-decreased proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-01

August 25, 1992


Driver seat

M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:21:57



Course: Belgian block
 Speed: 5 mph
 Note: Bobtail

HSEL: Health and safety exposure limit
 FDPB: Fatigue-decreased proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-02

August 25, 1992


Passenger seat

M916 ride quality

Exposure: 10h 0m



19-AUG-92 8:21:38



Course: Belgian block
 Speed: 10 mph
 Note: Bobtail


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-02
 August 25, 1992

Driver seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:21:38



Course: Belgian block
 Speed: 10 mph
 Note: Bobtail

HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-03

August 25, 1992

Passenger seat

M916 ride quality

Exposure: 10h 0m



Course: Belgian block
 Speed: 15 mph
 Note: Bobtail

HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage probability boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-03

August 25, 1992


Driver seat

M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:21:38



Course: Belgian block
 Speed: 15 mph
 Note: Bobtail


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage probability boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical

RUN-04
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



Course: Belgian block
 Speed: 20 mph
 Note: Bobtail


HSEL: Health and safety exposure limit
 FDPB: Foreign-dominated proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical

RUN-04
 August 25, 1992

Driver seat
 M916 ride quality

Exposure: 10h 0m



Course: Belgian block
 Speed: 20 mph
 Note: Bobtail


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-05
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:00



Course: Belgian block
 Speed: 5 mph
 Note: Unloaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-decreased proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-05
 August 25, 1992

Driver seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:00



Course: Belgian block
 Speed: 5 mph
 Note: Unloaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-decreased proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-06
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:00



Course: Belgian block
 Speed: 10 mph
 Note: Unloaded trailer

HSEL: Health and safety exposure limit
 FDPB: Fatigue-decreased proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-06

August 25, 1992


Driver seat

M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:00



Course: Belgian block
 Speed: 10 mph
 Note: Unloaded trailer

HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)


X: Longitudinal
 Y: Transverse
 Z: Vertical

RUN-07


August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:01



Course: Belgian block
 Speed: 15 mph
 Note: Unloaded trailer

HSEL: Health and safety exposure limit
 FDPB: Fatigue-determined proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-07

August 25, 1992


Driver seat

M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:01



Course: Belgian block
 Speed: 15 mph
 Note: Unloaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. combination (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-08
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:01



Course: Belgian block
 Speed: 20 mph.
 Note: Unloaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage probability boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. combination (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-08
 August 25, 1992

Driver seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:01



Course: Belgian block
 Speed: 20 mph
 Note: Unloaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage probability boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-09
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:02



Course: Belgian block
 Speed: 5 mph
 Note: Loaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. combination (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-09
 August 25, 1992

Driver seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:02



Course: Belgian block
 Speed: 5 mph
 Note: Loaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage preliminary boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-10
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:02



Course: Belgian block
 Speed: 10 mph
 Note: Loaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-decreased proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-10
 August 25, 1992

Driver seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-92 8:22:02



Course: Belgian block
 Speed: 10 mph
 Note: Loaded trailer

HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage probability boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-11

August 25, 1992


Passenger seat

M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:03



Course: Belgian block
 Speed: 15 mph
 Note: Loaded trailer


HSEL: Health and safety exposure limit
 FDPB: Foreign-dominated proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-11
 August 25, 1992

Driver seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-92 8:22:03



Course: Belgian block
 Speed: 15 mph
 Note: Loaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-12
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:03



Course: Belgian block
 Speed: 20 mph
 Note: Loaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-12
 August 25, 1992

Driver seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:03



Course: Belgian block
 Speed: 20 mph
 Note: Loaded trailer

HSEL: Health and safety exposure limit
 FDPB: Fatigue-damened proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)


X: Longitudinal
 Y: Transverse
 Z: Vertical

RUN-13


August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:04



Course: Cross country #2
 Speed: 12 mph
 Note: Loaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-dyscomfort proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-13
 August 25, 1992

Driver seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:04



Course: Cross country #2
 Speed: 12 mph
 Note: Loaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damaged proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-14
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:04



Course: Cross country #2
 Speed: 10 mph
 Note: Loaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damaged probability boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-14
 August 25, 1992

Driver seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-92 8:22:04



Course: Cross country #2
 Speed: 10 mph
 Note: Loaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-15
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:05



Course: Cross country #2
 Speed: 8 mph
 Note: Loaded trailer

HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-15

August 25, 1992


Driver seat

M916 ride quality

Exposure: 10h 0m



19-AUG-92 8:22:05



Course: Cross country #2
 Speed: 8 mph
 Note: Loaded trailer

HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage preliminary boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-16

August 25, 1992


Passenger seat

M916 ride quality

Exposure: 10h 0m



19-AUG-92 8:22:05



Course: Cross country #2
 Speed: 6 mph
 Note: Loaded trailer

HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-16

August 25, 1992


Driver seat

M916 ride quality

Exposure: 10h 0m



19-AUG-92 8:22:05



Course: Cross country #2
 Speed: 6 mph
 Note: Loaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-dominated proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-17
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:06



Course: Cross country #2
 Speed: 12 mph
 Note: Unloaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. combination (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-17
 August 25, 1992

Driver seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-92 8:22:06



Course: Cross country #2
 Speed: 12 mph
 Note: Unloaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-doseated proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical

RUN-18
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



Course: Cross country #2
 Speed: 10 mph
 Note: Unloaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damaged proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. combination (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-18
 August 25, 1992

Driver seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:06



Course: Cross country #2
 Speed: 10 mph
 Note: Unloaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damened proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-19
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-92 8:22:07



Course: Cross country #2
 Speed: 8 mph
 Note: Unloaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-19
 August 25, 1992

Driver seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-92 8:22:07



Course: Cross country #2
 Speed: 8 mph
 Note: Unloaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-20
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:07



Course: Cross country #2
 Speed: 6 mph
 Note: Unloaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-20
 August 25, 1992

Driver seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:07



Course: Cross country #2
 Speed: 6 mph
 Note: Unloaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage probability boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-21
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:08



Course: Cross country #2
 Speed: 12 mph
 Note: Bobtail


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage preliminary boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-21
 August 25, 1992

Driver seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-92 8:22:08



Course: Cross country #2
 Speed: 12 mph
 Note: Bobtail


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage probability boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. combination (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-22
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:08



Course: Cross country #2
 Speed: 10 mph
 Note: Bobtail


HSEL: Health and safety exposure limit
 FDPB: Fatigue-discomfort proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-22
 August 25, 1992

Driver seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:08



Course: Cross country #2
 Speed: 10 mph
 Note: Bobtail


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-23
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:09



Course: Cross country #2
 Speed: 8 mph
 Note: Bobtail

HSEL: Health and safety exposure limit
 FDPB: Fatigue-damaged probability boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-23

August 25, 1992


Driver seat

M916 ride quality

Exposure: 10h 0m



19-AUG-92 8:22:09



Course: Cross country #2
 Speed: 8 mph
 Note: Bobtail


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage probability boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. combination (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-24
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-92 8:22:09



Course: Cross country #2
 Speed: 6 mph
 Note: Bobtail


MSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-24
 August 25, 1992

Driver seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:09



Course: Cross country #2
 Speed: 6 mph
 Note: Bobtail


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-25
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:10



Course: Paved
 Speed: 25 mph
 Note: Bobtail


HSEL: Health and safety exposure limit
 FDPB: Fatigue-decreased proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-25
 August 25, 1992

Driver seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-92 8:22:10



Course: Paved
 Speed: 25 mph
 Note: Bobtail


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage and proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-26
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:10



Course: Paved
 Speed: 35 mph
 Note: Bobtail


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage preliminary boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-26
 August 25, 1992

Driver seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:10



Course: Paved
 Speed: 35 mph
 Note: Bobtail

HSEL: Health and safety exposure limit
 FDPB: Fatigue-decreased proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-27

August 25, 1992

Passenger seat

M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:10



Course: Paved
 Speed: 45 mph
 Note: Bobtail


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage probability boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-27
 August 25, 1992

Driver seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:10



Course: Paved
 Speed: 45 mph
 Note: Bobtail


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage-d profile boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. combination (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-28
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:11



Course: Paved
 Speed: 55 mph
 Note: Bobtail

HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-28

August 25, 1992


Driver seat

M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:11



Course: Paved
 Speed: 55 mph
 Note: Bobtail


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-29
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:11



Course: Paved
 Speed: 25 mph
 Note: Unloaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue discomfort proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. combination (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-29
 August 25, 1992

Driver seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:11



Course: Paved
 Speed: 25 mph
 Note: Unloaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage probability boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-30
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:11



Course: Paved
 Speed: 35 mph
 Note: Unloaded trailer

HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage preliminary boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. combination (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-30

August 25, 1992


Driver seat

M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:11



Course: Paved
 Speed: 35 mph
 Note: Unloaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage probability boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. combination (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-31
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-92 8:22:12



Course: Paved
 Speed: 45 mph
 Note: Unloaded trailer

HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage probability boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. combination (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-31

August 25, 1992


Driver seat

M916 ride quality

Exposure: 10h 0m



19-AUG-92 8:22:12



Course: Paved
 Speed: 45 mph
 Note: Unloaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage probability boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-32
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-92 8:22:12



Course: Paved
 Speed: 55 mph
 Note: Unloaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCS: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-32
 August 25, 1992

Driver seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:12



Course: Paved
 Speed: 55 mph
 Note: Unloaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-33
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:13



Course: Paved
 Speed: 25 mph
 Note: Loaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage probability boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-33
 August 25, 1992

Driver seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:13



Course: Paved
 Speed: 25 mph
 Note: Loaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-34
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:13



Course: Paved
 Speed: 35 mph
 Note: Loaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-34
 August 25, 1992

Driver seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:13



Course: Paved
 Speed: 35 mph
 Note: Loaded trailer

HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-35

August 25, 1992


Passenger seat

M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:13



Course: Paved
 Speed: 45 mph
 Note: Loaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-decreased proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-35
 August 25, 1992

Driver seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:13



Course: Paved
 Speed: 45 mph
 Note: Loaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage proficiency boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-36
 August 25, 1992

Passenger seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:14



Course: Paved
 Speed: 55 mph
 Note: Loaded trailer


HSEL: Health and safety exposure limit
 FDPB: Fatigue-damage probability boundary
 RCB: Reduced comfort boundary
 RMS: Vibration R.M.S. acceleration (m/s²)

X: Longitudinal
 Y: Transverse
 Z: Vertical


RUN-36
 August 25, 1992

Driver seat
 M916 ride quality

Exposure: 10h 0m



19-AUG-93 8:22:14



Course: Paved
 Speed: 55 mph
 Note: Loaded trailer

Initial distribution

Commander, U.S. Army Natick Research,
Development and Engineering Center
ATTN: SATNC-MIL (Documents
Librarian)
Natick, MA 01760-5040

U.S. Army Communications-Electronics
Command
ATTN: AMSEL-RD-ESA-D
Fort Monmouth, NJ 07703

Commander
10th Medical Laboratory
ATTN: Audiologist
APO New York 09180

Naval Air Development Center
Technical Information Division
Technical Support Detachment
Warminster, PA 18974

Commanding Officer, Naval Medical
Research and Development Command
National Naval Medical Center
Bethesda, MD 20814-5044

Deputy Director, Defense Research
and Engineering
ATTN: Military Assistant
for Medical and Life Sciences
Washington, DC 20301-3080

Commander, U.S. Army Research
Institute of Environmental Medicine
Natick, MA 01760

Library
Naval Submarine Medical Research Lab
Box 900, Naval Sub Base
Groton, CT 06349-5900

Director, U.S. Army Human
Engineering Laboratory
ATTN: Technical Library
Aberdeen Proving Ground, MD 21005

Commander
Man-Machine Integration System
Code 602
Naval Air Development Center
Warminster, PA 18974

Commander
Naval Air Development Center
ATTN: Code 602-B (Mr. Brindle)
Warminster, PA 18974

Commanding Officer
Armstrong Laboratory
Wright-Patterson
Air Force Base, OH 45433-6573

Director
Army Audiology and Speech Center
Walter Reed Army Medical Center
Washington, DC 20307-5001

Commander/Director
U.S. Army Combat Surveillance
and Target Acquisition Lab
ATTN: DELCS-D
Fort Monmouth, NJ 07703-5304

Commander, U.S. Army Institute
of Dental Research
ATTN: Jean A. Setterstrom, Ph. D.
Walter Reed Army Medical Center
Washington, DC 20307-5300

Commander, U.S. Army Test
and Evaluation Command
ATTN: AMSTE-AD-H
Aberdeen Proving Ground, MD 21005

Naval Air Systems Command
Technical Air Library 950D
Room 278, Jefferson Plaza II
Department of the Navy
Washington, DC 20361

Director
U.S. Army Ballistic
Research Laboratory
ATTN: DRXBR-OD-ST Tech Reports
Aberdeen Proving Ground, MD 21005

Commander
U.S. Army Medical Research
Institute of Chemical Defense
ATTN: SGRD-UV-AO
Aberdeen Proving Ground,
MD 21010-5425

Commander, U.S. Army Medical
Research and Development Command
ATTN: SGRD-RMS (Ms. Madigan)
Fort Detrick, Frederick, MD 21702-5012

Director
Walter Reed Army Institute of Research
Washington, DC 20307-5100

HQ DA (DASG-PSP-O)
5109 Leesburg Pike
Falls Church, VA 22041-3258

Harry Diamond Laboratories
ATTN: Technical Information Branch
2800 Powder Mill Road
Adelphi, MD 20783-1197

U.S. Army Materiel Systems
Analysis Agency
ATTN: AMXSYP-PA (Reports Processing)
Aberdeen Proving Ground
MD 21005-5071

U.S. Army Ordnance Center
and School Library
Simpson Hall, Building 3071
Aberdeen Proving Ground, MD 21005

U.S. Army Environmental
Hygiene Agency
Building E2100
Aberdeen Proving Ground, MD 21010

Technical Library Chemical Research
and Development Center
Aberdeen Proving Ground, MD
21010-5423

Commander
U.S. Army Medical Research
Institute of Infectious Disease
SGRD-UIZ-C
Fort Detrick, Frederick, MD 21702

Director, Biological
Sciences Division
Office of Naval Research
600 North Quincy Street
Arlington, VA 22217

Commander
U.S. Army Materiel Command
ATTN: AMCDE-XS
5001 Eisenhower Avenue
Alexandria, VA 22333

Commandant
U.S. Army Aviation
Logistics School ATTN: ATSQ-TDN
Fort Eustis, VA 23604

Headquarters (ATMD)
U.S. Army Training
and Doctrine Command
ATTN: ATBO-M
Fort Monroe, VA 23651

IAF Liaison Officer for Safety
USAF Safety Agency/SEFF
9750 Avenue G, SE
Kirtland Air Force Base
NM 87117-5671

Naval Aerospace Medical
Institute Library
Building 1953, Code 03L
Pensacola, FL 32508-5600

Command Surgeon
HQ USCENTCOM (CCSG)
U.S. Central Command
MacDill Air Force Base, FL 33608

Air University Library
(AUL/LSE)
Maxwell Air Force Base, AL 36112

U.S. Air Force Institute
of Technology (AFIT/LDEE)
Building 640, Area B
Wright-Patterson
Air Force Base, OH 45433

Henry L. Taylor
Director, Institute of Aviation
University of Illinois-Willard Airport
Savoy, IL 61874

Chief, National Guard Bureau
ATTN: NGB-ARS (COL Urbauer)
Room 410, Park Center 4
4501 Ford Avenue
Alexandria, VA 22302-1451

Commander
U.S. Army Aviation Systems Command
ATTN: SGRD-UAX-AL
4300 Goodfellow Blvd., Building 105
St. Louis, MO 63120

U.S. Army Aviation Systems Command
Library and Information Center Branch
ATTN: AMSAV-DIL
4300 Goodfellow Boulevard
St. Louis, MO 63120

Federal Aviation Administration
Civil Aeromedical Institute
Library AAM-400A
P.O. Box 25082
Oklahoma City, OK 73125

Commander
U.S. Army Academy
of Health Sciences
ATTN: Library
Fort Sam Houston, TX 78234

Commander
U.S. Army Institute of Surgical Research
ATTN: SGRD-USM (Jan Duke)
Fort Sam Houston, TX 78234-6200

AAMRL/HEX
Wright-Patterson
Air Force Base, OH 45433

John A. Dellinger,
Southwest Research Institute
P. O. Box 28510
San Antonio, TX 78284

Product Manager
Aviation Life Support Equipment
ATTN: AMCPM-ALSE
4300 Goodfellow Boulevard
St. Louis, MO 63120-1798

Commander and Director
USAE Waterways Experiment Station
ATTN: CEWES-IM-MI-R

Alfrieda S. Clark, CD Department
3909 Halls Ferry Road
Vicksburg, MS 39180-6199

Commanding Officer
Naval Biodynamics Laboratory
P.O. Box 24907
New Orleans, LA 70189-0407

Assistant Commandant
U.S. Army Field Artillery School
ATTN: Morris Swott Technical Library
Fort Sill, OK 73503-0312

Mr. Peter Seib
Human Engineering Crew Station
Box 266
Westland Helicopters Limited
Yeovil, Somerset BA20 2YB UK

U.S. Army Dugway Proving Ground
Technical Library, Building 5330
Dugway, UT 84022

U.S. Army Yuma Proving Ground
Technical Library
Yuma, AZ 85364

AFFTC Technical Library
6510 TW/TSTL
Edwards Air Force Base,
CA 93523-5000

Commander
Code 3431
Naval Weapons Center
China Lake, CA 93555

Aeromechanics Laboratory
U.S. Army Research and Technical Labs
Ames Research Center, M/S 215-1
Moffett Field, CA 94035

Sixth U.S. Army
ATTN: SMA
Presidio of San Francisco, CA 94129

Commander
U.S. Army Aeromedical Center
Fort Rucker, AL 36362

Strughold Aeromedical Library
Document Service Section
2511 Kennedy Circle
Brooks Air Force Base, TX 78235-5122

Dr. Diane Damos
Department of Human Factors
ISSM, USC
Los Angeles, CA 90089-0021

U.S. Army White Sands
Missile Range
ATTN: STEWS-IM-ST
White Sands Missile Range, NM 88002

U.S. Army Aviation Engineering
Flight Activity
ATTN: SAVTE-M (Tech Lib) Stop 217
Edwards Air Force Base, CA 93523-5000

Ms. Sandra G. Hart
Ames Research Center
MS 262-3
Moffett Field, CA 94035

Commander, Letterman Army Institute
of Research
ATTN: Medical Research Library
Presidio of San Francisco, CA 94129

Commander
U.S. Army Medical Materiel
Development Activity
Fort Detrick, Frederick, MD 21702-5009

Commander
U.S. Army Health Services Command
ATTN: HSOP-SO
Fort Sam Houston, TX 78234-6000

U. S. Army Research Institute
Aviation R&D Activity
ATTN: PERI-IR
Fort Rucker, AL 36362

Commander
U.S. Army Safety Center
Fort Rucker, AL 36362

U.S. Army Aircraft Development
Test Activity
ATTN: STEBG-MP-P
Cairns Army Air Field
Fort Rucker, AL 36362

Commander, U.S. Army Medical Research
and Development Command
ATTN: SGRD-PLC (COL Schnakenberg)
Fort Detrick, Frederick, MD 21702

TRADOC Aviation LO
Unit 21551, Box A-209-A
APO AE 09777

Netherlands Army Liaison Office
Building 602
Fort Rucker, AL 36362

British Army Liaison Office
Building 602
Fort Rucker, AL 36362

Italian Army Liaison Office
Building 602
Fort Rucker, AL 36362

Directorate of Training Development
Building 502
Fort Rucker, AL 36362

Chief
USAHEL/USAAVNC Field Office
P. O. Box 716
Fort Rucker, AL 36362-5349

Commander, U.S. Army Aviation Center
and Fort Rucker
ATTN: ATZQ-CG
Fort Rucker, AL 36362

Chief
Test & Evaluation Coordinating Board
Cairns Army Air Field
Fort Rucker, AL 36362

MAJ Terry Newman
Canadian Army Liaison Office
Building 602
Fort Rucker, AL 36362

German Army Liaison Office
Building 602
Fort Rucker, AL 36362

French Army Liaison Office
USAAVNC (Building 602)
Fort Rucker, AL 36362-5021

Australian Army Liaison Office
Building 602
Fort Rucker, AL 36362

Dr. Garrison Rapmund
6 Burning Tree Court
Bethesda, MD 20817

Commandant, Royal Air Force
Institute of Aviation Medicine
Farnborough, Hampshire GU14 6SZ UK

Commander
U.S. Army Biomedical Research
and Development Laboratory
ATTN: SGRD-UBZ-I
Fort Detrick, Frederick, MD 21702

Defense Technical Information
Cameron Station, Building 5
Alexandra, VA 22304-6145

Commander, U.S. Army Foreign Science
and Technology Center
AIFRTA (Davis)
220 7th Street, NE
Charlottesville, VA 22901-5396

Director,
Applied Technology Laboratory
USARTL-AVSCOM
ATTN: Library, Building 401
Fort Eustis, VA 23604

Commander, U.S. Air Force
Development Test Center
101 West D Avenue, Suite 117
Eglin Air Force Base, FL 32542-5495

Aviation Medicine Clinic
TMC #22, SAAF
Fort Bragg, NC 28305

Dr. H. Dix Christensen
Bio-Medical Science Building, Room 753
Post Office Box 26901
Oklahoma City, OK 73190

Commander, U.S. Army Missile
Command
Redstone Scientific Information Center
ATTN: AMSMI-RD-CS-R
/ILL Documents
Redstone Arsenal, AL 35898

Director
Army Personnel Research Establishment
Farnborough, Hants GU14 6SZ UK

U.S. Army Research and Technology
Laboratories (AVSCOM)
Propulsion Laboratory MS 302-2
NASA Lewis Research Center
Cleveland, OH 44135

COL John F. Glenn
U.S. Army Medical Research
& Development Command
SGRD-ZC
Fort Detrick, Frederick, MD 21702-5012

Dr. Eugene S. Channing
7985 Schooner Court
Frederick, MD 21701-3273

USAMRDC Liaison at Academy
of Health Sciences
ATTN: HSHA-ZAC-F
Fort Sam Houston, TX 78234

Dr. A. Kornfield, President
Biosearch Company
3016 Revere Road
Drexel Hill, PA 29026

NVESD
AMSEL-RD-NV-ASID-PST
(Attn: Trang Bui)
10221 Burbeck Road
Fort Belvoir, VA 22060-5806

CA Av Med
HQ DAAC
Middle Wallop
Stockbridge, Hants S020 8DY UK

Dr. Christine Schlichting
Behavioral Sciences Department
Box 900, NAVUBASE NLON
Groton, CT 06349-5900

COL C. Fred Tyner
U.S. Army Medical Research
& Development Command
SGRD-ZB
Fort Detrick, Frederick, MD 21702-5012

Director
Directorate of Combat Developments
ATZQ-CD
Building 515
Fort Rucker, AL 36362